

Principal dimensions (mm)						Basic load ratings(N)		Basic load ratings(kgf)		Speed ratings(rpm)			Designation				Abutment and fillet dimensions (mm)						Weight(g)		
外形尺寸						额定载荷(N)		额定载荷(kgf)		极限转速(rpm)			轴承代号				安装尺寸(mm)						重量(g)		
d	D	B	B1	r ⁽¹⁾		Cr	Cor	Cr	Cor	Grease 脂润滑		Oil 油润滑		Open type 开放型	With shielded 防尘盖型	With seal VV 密封式VV	With seal DD 密封式DD	d _a Min(最小)	d _b Max(最大)	D _a Max(最大)	D _b Min(最小)	r _a Max(最大)	r _b Max(最大)	Open type 开放型	With shielded 防尘盖型
				Min(最小)	Min(最小)					ZZ	D-D	Z													
1.5	6	2.5	3	0.15	0.15	330	98	34	10	75000	-	90000	601X	601XZZ	-	-	2.7	3	4.8	5.04	0.15	0.15	0.33	0.38	
2	7	2.8	3.5	0.15	0.15	385	127	39	13	63000	-	75000	602	602ZZ	-	-	3.2	3.8	5.8	6.2	0.15	0.15	0.51	0.58	
2.5	8	2.8	4	0.15	0.15	550	175	56	18	60000	-	71000	602X	602XZZ	-	-	3.7	4.1	6.8	7	0.15	0.15	0.63	0.83	
3	9	3	5	0.15	0.15	570	187	58	19	56000	-	67000	603	603ZZ	-	-	4.2	4.3	7.8	7.9	0.15	0.15	0.87	1.45	
4	12	4	4	0.2	0.2	960	345	98	35	48000	-	56000	604	604ZZ	-	-	5.6	5.6	10.4	9.9	0.2	0.2	2.25	2.29	
5	14	5	5	0.2	0.2	1330	505	135	52	40000	38000	50000	605	605ZZ	-	605DD	6.6	6.9	12.4	12.2	0.2	0.2	3.54	3.48	
6	17	6	6	0.3	0.3	2260	835	231	85	38000	34000	45000	606	606ZZ	606VV	606DD	8	8.2	15	14.8	0.3	0.3	5.97	6.08	
7	19	6	6	0.3	0.3	2340	885	238	90	36000	32000	43000	607	607ZZ1	607VV	607DD	9	9.1	17	16.5	0.3	0.3	7.67	7.51	
8	22	7	7	0.3	0.3	3300	1370	335	140	34000	28000	40000	608	608ZZ	608VV	608DD	10	10.5	20	19	0.3	0.3	12.1	12.2	
9	24	7	7	0.3	0.3	3350	1430	340	146	32000	24000	38000	609	609ZZ	609VV	609DD	11	12	22.8	20.5	0.3	0.3	14.5	14.7	