

Principal dimensions (mm)						Basic load ratings(N)		Basic load ratings(kgf)		Speed ratings(rpm)			Designation				Abutment and fillet dimensions (mm)						Weight(g)	
外形尺寸						额定载荷(N)		额定载荷(kgf)		极限转速(rpm)			轴承代号				安装尺寸(mm)						重量(g)	
d	D	B	B1	$r_1^{(1)}$	$r1^{(1)}$	Cr	Cor	Cr	Cor	Grease 脂润滑		Oil 油润滑	Open type	With shield	With seal VV	With seal DD	$d_a$	$d_b$	Da	Db	$r_a$	$r_b$	Open type	With shield
				Min (最小)	Min (最小)					ZZ	D-D	Z	开放型	防尘盖型	密封式VV	密封式DD								
3	10	4	4	0.15	0.15	630	218	64	22	50000	-	60000	623	623ZZ	-	-	4.2	4.3	8.8	8	0.15	0.15	1.65	1.66
4	13	5	5	0.2	0.2	1300	485	133	49	40000	-	48000	624	624ZZ	-	-	5.6	6	11.4	11.3	0.2	0.2	3.03	3.04
5	16	5	5	0.3	0.3	1730	670	177	68	36000	32000	43000	625	625ZZ1	625VV	625DD	7	7.5	14	13.8	0.3	0.3	4.95	4.86
6	19	6	6	0.3	0.3	2340	885	238	90	32000	30000	40000	626	626ZZ1	626VV	626DD	8	8.5	17	16.5	0.3	0.3	8.15	7.94
7	22	7	7	0.3	0.3	3300	1370	335	140	30000	28000	36000	627	627ZZ	627VV	627DD	9	10.5	20	19	0.3	0.3	12.7	12.9
8	24	8	8	0.3	0.3	3350	1430	340	146	28000	24000	34000	628	628ZZ	628VV	628DD	10	12	22	20.5	0.3	0.3	17.2	17.4
9	26	8	8	-0.6	-0.6	4550	1970	465	201	28000	22000	34000	629	629ZZ	629VV	629DD	11	12.8	24	22.8	0.3	0.3	19.5	19.3