

Principal dimensions (mm)						Basic load ratings(N)		Basic load ratings(kgf)		Speed ratings(rpm)			Designation				Abutment and fillet dimensions (mm)						Weight(g)		
外形尺寸						额定载荷(N)		额定载荷(kgf)		极限转速(rpm)			轴承代号				安装尺寸(mm)						重量(g)		
d	D	B	B1	r ⁽¹⁾	r ⁽¹⁾	Cr	Cor	Cr	Cor	Grease 脂润滑		Oil 油润滑		Open type	With shielded	With seal VV	With seal DD	d _a	d _b	Da	Db	r _a	r _b	Open type	With shielded
				Min (最小)	Min (最小)					ZZ	D-D	Z	开放型												
3	13	5	5	0.2	0.2	1300	485	133	49	40000	-	48000	633	633ZZ	-	-	-	4.6	6	11.4	11.3	0.2	0.2	3.38	3.33
4	16	5	5	0.3	0.3	1730	670	177	68	36000	-	43000	634	634ZZ1	-	-	-	6	7.5	14	13.8	0.3	0.3	5.24	5.21
5	19	6	6	0.3	0.3	2340	885	238	90	32000	30000	40000	635	635ZZ1	635VV	635DD	7	8.5	17	16.5	0.3	0.3	8.56	8.34	
6	22	7	7	0.3	0.3	3300	1370	335	140	30000	28000	36000	636	636ZZ	636VV	636DD	8	10.5	20	19	0.3	0.3	14	14	
7	26	9	9	0.3	0.3	4550	1970	465	201	28000	22000	34000	637	637ZZ1	637VV	637DD	9	12.8	24	22.8	0.3	0.3	24	25	
8	28	9	9	0.3	0.3	4550	1970	465	201	28000	22000	34000	638	638ZZ1	638VV	638DD	10	12.8	26	22.8	0.3	0.3	28.3	28.6	
9	30	10	10	0.6	0.6	5100	2390	520	244	24000	-	30000	639	639ZZ	639VV	-	-	13	16.1	26	25.6	0.6	0.6	36.5	36