

Principal dimensions (mm)						Basic load ratings(N)		Basic load ratings(kgf)		Speed ratings(rpm)			Designation				Abutment and fillet dimensions (mm)						Weight(g)		
外形尺寸						额定载荷(N)		额定载荷(kgf)		极限转速(rpm)			轴承代号				安装尺寸(mm)						重量(g)		
d	D	B	B1	r ⁽¹⁾		Cr	Cor	Cr	Cor	Grease 脂润滑		Oil 油润滑		Open type 开放型	With shield 防尘盖型	With seal VV 密封式VV	With seal DD 密封式DD	d _a Min (最小)	d _b Max (最大)	D _a Max (最大)	D _b Min (最小)	r _a Max (最大)	r _b Max (最大)	Open type 开放型	With shield 防尘盖型
				Min (最小)	Min (最小)					ZZ	D-D	Z													
1	4	1.6	-	0.1	-	38	35	14	3.5	100000	-	120000	691	-	-	-	1.8	-	3.2	-	0.1	-	0.09	-	
1.5	5	2	2.6	0.15	0.15	237	69	24	7	85000	-	100000	691X	691XZZ	-	-	2.7	2.5	3.8	4.3	0.15	0.15	0.17	0.2	
2	6	2.3	3	0.15	0.15	330	98	34	10	75000	-	90000	692	692ZZ	-	-	3.2	3	4.8	5.4	0.15	0.15	0.28	0.38	
2.5	7	2.5	3.5	0.15	0.15	385	127	39	13	63000	-	75000	692X	692XZZ	-	-	3.7	3.8	5.8	6.2	0.15	0.15	0.41	0.55	
3	8	3	4	0.15	0.15	560	179	57	18	60000	-	67000	693	693ZZ	-	-	4.2	4.3	6.8	7.3	0.15	0.15	0.61	0.83	
4	11	4	4	0.15	0.15	960	345	98	35	48000	-	56000	694	694ZZ	-	-	5.2	5.6	9.8	9.9	0.15	0.15	1.7	1.75	
5	13	4	4	0.2	0.2	1080	430	110	44	43000	40000	50000	695	695ZZ	695VV	695DD	6.6	6.6	11.4	11.2	0.2	0.2	2.45	2.5	
6	15	5	5	0.2	0.2	1730	670	177	68	40000	36000	45000	696	696ZZ1	696VV	696DD	7.6	7.9	13.4	13.3	0.2	0.2	3.88	3.72	
7	17	5	5	0.3	0.3	1610	710	164	73	36000	28000	43000	697	697ZZ1	697VV	697DD	9	10.2	15	14.8	0.3	0.3	5.26	5.12	
8	19	6	6	0.3	0.3	2240	910	228	93	36000	28000	43000	698	698ZZ	698VV	698DD	10	10	17	16.5	0.3	0.3	7.23	7.18	
9	20	6	6	0.3	0.3	1720	840	175	86	34000	24000	40000	699	699ZZ1	699VV	699DD	11	12	18	17.2	0.3	0.3	8.45	8.33	