

Dimensions(mm)				Basic load ratings(KN)		Limiting Speed (rpm)		Designation	Weight(Kg)
外形尺寸(毫米)				基本额定负荷 (千牛)		极限转速(转/分)		型号	重量
						Grease 脂润滑	Oil 油润滑		(千克)
90	140	24	1.5	40.3	42.5	3900	5200	6018M	1.1
95	145	24	1.5	42.3	46.5	3700	4900	6019M	1.15
100	150	24	1.5	44.2	50.6	3500	4700	6020M	1.2
110	170	28	2	55	62.5	3100	4100	6022M	1.89
120	180	28	2	57.1	68.2	2900	3800	6024M	2.1
130	200	33	2	74.3	87.2	2600	3400	6026M	3.08
140	210	33	2	80.9	102	2400	3200	6028M	4.11
150	225	35	2.1	85	110	2200	2900	6030M	5.24
150	230	35	2.1	85	110	2200	2900	6030X1M	5.5
160	240	38	2.1	85.8	118	2000	2700	6032M	6.54
170	260	42	2.1	97	137	1900	2500	6034M	8.53
170	265	42	2.1	97	137	1900	2500	6034X2-1M	9
170	270	42	2.1	97	137	1800	2400	6034X2-2M	9.6
180	280	46	2.1	134	180	1700	2300	6036M	11.1
190	290	46	2.1	144	200	1600	2200	6038M	11.5
200	310	51	2.1	159	225	1500	2000	6040M	15.2
220	340	56	3	172	265	1350	1800	6044M	20.4
240	359.5	56	3	177	286	1230	1640	6048X1M	19.7
240	360	56	3	177	286	1230	1640	6048M	20.4
260	400	65	4	224	376	1080	1440	6052M	31
280	420	65	4	232	407	1000	1340	6056M	32.9
300	380	38	2.1	114	198	1040	1390	61860M	10.7
300	419.5	56	3	198	349	960	1290	61960X1M	25
300	420	56	3	198	349	960	1290	61960M	25.1
300	459.5	74	1	257	473	900	1220	6060X1M	47.5
300	460	74	4	257	473	900	1220	6060M	47.6
320	480	74	4	269	509	850	1130	6064M	48.7
340	520	82	5	310	596	800	1050	6068M	62
360	540	82	5	324	649	760	1000	6072M	64.5
380	560	82	5	336	699	720	950	6076M	67.5
400	600	90	5	361	751	670	880	6080M	87.5
420	620	90	5	376	814	630	830	6084M	91.5