

外形尺寸(毫米)				基本额定负荷		极限转速(转/分)		型号	重量
Boundary dimensions(mm)				(千牛)		Speed rating			(千克)
				Basic load ratings(kN)		(rpm)		Designations	Weight
d	D	B	rmin	Cr	Cor	脂润滑 Grease	油润滑 Oil		Designations
120	180	28	2	132	202	3200	3600	N1024M	
120	215	40	2.1	260	365	2400	3000	N224M	10.5
120	215	58	2.1	370	580	2400	3000	N2224M	9.74
120	215	58	2.1	420	635	2400	3000	N2224E	8.82
120	260	55	3	465	600	1700	2200	N324M	15.2
120	260	86	3	660	950	1700	2200	N2324M	23.9
120	310	72	5	560	700	1700	2200	N424M	29.8
130	200	33	2	150	220	3000	3600	N1026M	3.91
130	230	40	3	270	390	2200	2800	N226M	7.49
130	230	64	3	420	680	2200	2800	N2226M	19.8
130	280	58	4	520	680	1600	2000	N326M	18.6
130	280	93	4	770	1140	1600	2000	N2326M	30.1
130	340	78	5	760	980	1700	2000	N426M	39.1
140	210	33	2	170	263	2800	3200	N1028M	4.11
140	250	42	3	320	460	2000	2600	N228M	9.41
140	250	68	3	480	760	2000	2600	N2228M	15.1
140	300	62	4	570	760	1800	2200	N328M	22.7
140	300	102	4	890	1300	1800	2200	N2328M	37.5
140	360	82	5	880	1200	1600	1900	N428M	47.5
150	270	45	3	360	540	1900	2400	N230M	11.9
150	320	65	4	630	840	1700	2000	N330M	27.3
150	320	108	4	940	1420	1700	2000	N2330M	45.1
160	290	48	3	420	630	1800	2200	N232M	10.6
160	340	68	4	660	920	1500	1800	N332M	31.7
170	310	52	4	480	730	1600	2000	N234M	18.4
170	360	72	4	760	1040	1500	1800	N334M	36.6
180	320	52	4	480	740	1600	1900	N236M	18.9
180	380	75	4	830	1200	1400	1700	N336M	39.7
190	340	55	4	540	840	1500	1800	N238M	22.9
190	400	78	5	1000	1500	1100	1400	N338M	50.4
200	310	51	2.1	370	600	1800	2200	N1040M	13.2
200	360	58	4	610	960	1400	1700	N240M	27.3
200	420	138	5	1570	2530	1200	1500	N2340M	102
220	400	65	4	730	1050	1400	1700	N244M	38.9
240	440	72	4	880	1380	1200	1500	N248M	51.6
260	400	65	4	740	1340	1400	1700	N1052M	30.8