

外形尺寸(毫米)				基本额定负荷(千牛)		极限转速(转/分)		型号	重量	相当于国外型号(参考)	
Boundary dimensions				Basic load ratings		Speed rating			(千克)	foreign models (reference)	
d	D	B	rmin	Cr	Cor	脂润滑	油润滑	Designations	Weight	SKF	FAG
(mm)				(kN)		Grease	Oil		(kg)		
130	210	80	2	142	235	1850	2500	4026X2D	9.7	-	-
140	209.5	66	2	134	237	1800	2400	4028X3D	8.28	309515D	538854
150	225	73	2.1	159	280	1600	2200	4030X2D	10.5	305286D	510776A
150	230	70	2.1	159	280	1600	2200	4030X3D	11.1	305283D	506963
160	215	56	1.8	132	204	1600	2200	4932X2DC	5.27	305608	514478
160	240	76	2	232	325	1450	1850	4032X2DC	12.3	305183	507511
170	259.5	84	2.1	208	385	1400	1900	4934X3D	16.7	-	-
180	259.5	66	2.1	153	293	1300	1800	4936X3D	12	305262D	509059A
190	269.5	66	2.1	163	318	1200	1700	4938X3D	11.6	305338D	508658A
200	279.5	76	2.1	201	387	1100	1600	4940X3D	14.8	305428D	508733A
200	289.5	76	2.1	221	439	1100	1600	4940X3D-1	17.3	305263D	509590A
220	309.5	76	3	238	491	1060	1400	4944X3D	18.5	305272D	511045A
230	329.5	80	3	203	423	1020	1400	4946X1D	22.9	305264D	508732A
240	359.5	118	3	315	706	1000	1300	4048X1D	44.1	-	-
240	370	112	3	314	707	1000	1300	4048X3D	47	-	-
240	440	144	3	475	1139	1000	1300	3248X2D	105	-	-
260	369.5	92	4	286	652	890	1200	4952X3D	30	305270D	508731
280	389.5	92	4	278	650	850	1100	4956X3D-1	31.9	305269D	508730
280	390	92	4	278	650	850	1100	4956X3D	32	-	-
300	419.5	112	4	350	863	800	1080	4960X3D	50.5	-	-
320	459.5	140	4	396	1022	740	1000	4064X3D	79.9	-	-