

Designations	Dimensions				Basic load ratings		Speed ratings		Installation dimensions			Weight
轴承代号	基本尺寸				基本额定载荷		极限转速		安装相关尺寸			重量
	d	D	B	rsmn	Cr	C0r	脂润滑 Grease	油润滑 Oil	dhmax	Dsmin	Rmax	
	mm				KN		rpm		mm			Kg
205	25	52	15	1	11	8	12000	15000	32	46	0.8	0.134
206	30	62	16	1	23.6	16	10000	13000	37.5	54	0.8	0.217
6208	40	80	18	1.1	29.1	17.9	8500	10000	51	69	0.8	0.369
6308	40	90	23	1.5	41	24	7500	9000	52.5	77.5	1	0.642
6009-2Z	45	75	16	1	20	14	9000	11000	52.4	67.5	0.8	0.245
6310	50	110	27	2	57.5	35	6300	7500	63	97	2	1.07
6011	55	90	18	1.1	24.2	18.4	7500	9000	63.5	81	0.8	0.384
6211	55	100	21	1.5	39	26.8	6300	7500	66.5	88.5	1	0.628
6311	55	120	29	2	67.5	43	5600	6700	72	107	1.5	1.38
212	60	110	22	1.5	53	33	5600	7100	68	102	1	0.793
6012	60	95	18	1.1	30	23	6700	8000	66.5	88.5	0.8	0.426
6212	60	110	22	1.5	53	33	5600	7100	68	102	1	0.793
6312	60	130	31	2.1	82	48.5	5300	6300	71	119	1.5	1.71
6013	65	100	18	1.1	32	25	6300	7500	71.5	93.5	0.8	0.428
6213	65	120	23	1.5	56	41	5300	6300	73	112	1.5	0.973
6313	65	140	33	2.1	92.5	59.5	4800	5600	76	129	2	2.1
6413	65	160	37	2.1	118	78.5	4500	6300	76	149	2	3.25
6014	70	110	20	1.1	38	31	6000	7000	76.5	103.5	0.8	0.62
6214	70	125	24	1.5	60.5	46	5000	6000	78	117	1	1.34
6314	70	150	35	2.1	104	68	4500	5300	81	139	1.5	2.55
6414	70	180	42	3	143	103	3800	4500	83	167	2.5	4.73
6015	75	115	20	1.1	38	31	5600	6700	81.5	108.5	0.8	0.63
6215M	75	130	25	1.5	66	50	4800	5600	83	122	1	1.45
6315	75	160	37	2.1	113	116	4300	5000	86	149	1.5	3.1
6415	75	190	45	3	153	114	3600	4300	88	177	2.5	5.57
61816	80	100	10	0.6	12.7	13.3	6000	7000	83.2	96.8	0.6	0.153
61916	80	110	16	1	27.5	25	5600	6700	85	105	0.8	0.35
6016	80	125	22	1.1	47.5	40	5300	6300	86.5	118.5	0.8	0.86
6017M	85	130	22	1.1	47.5	40	5000	6000	91.5	123.5	0.8	1.12
6217M	85	150	28	2	83	64	4300	5000	94	141	1.5	1.91
6317M	85	180	41	3	102	96.5	3800	4500	98	167	2.5	4.97
61918M	90	125	18	1.1	33	31.5	5000	6000	96.5	118.5	0.8	0.68
6018	90	140	24	1.5	58.5	50	4800	5600	98	132	1	1.16
6218	90	160	30	2	95.5	72	3800	4500	99	151	1.5	2.19
6318	90	190	43	3	144	108	3400	4000	103	177	2.5	4.97
6418	90	225	54	4	193	158	3000	3600	106	209	3.5	9.47
61820	100	125	13	1	19.6	21.2	4800	5600	105	120	0.8	0.326
6020	100	150	24	1.5	57.5	56.5	4300	5000	108	142	1	1.17
6220	100	180	34	2.1	122	93	3400	4000	111	169	1.5	3.2
6320	100	215	47	3	173	141	2800	3600	113	202	2.5	7.01
6420	100	250	58	4	224	195	2600	3400	116	234	3.5	12.8
6322	110	240	50	3	195	167	2400	3000	140	208	2.5	9.72
61924	120	165	22	1.1	53	54	3600	4300	130	154	1	1.21
6038M	190	290	46	2.1	165	175	2000	2600	216	264	1.5	11.1
6240	200	360	58	4	285	335	1700	2000	245	320	3	22.3
6240-Z	200	360	58	4	288	335	1700	2000	245	320	3	22.5
6044	220	340	56	3	230	270	1800	2200	254	314.2	2	15.5
61948M	240	320	38	2.1	153	186	1800	2200	260	302	2	8.5
6048M	240	360	56	3	255	315	1700	2000	269	330	2.5	20.7
61952M	260	360	46	2.1	212	269	1600	1900	284	336	2	14.4
6052M	260	400	65	4	294	373	1500	1800	295	364	3	28.4
61956M	280	380	46	2.1	215	282	1500	1800	303	356	2	16.4
6060	300	460	74	4	340	480	1200	1500	341	418	3	48.4
61960	300	420	56	3	205	370	1300	1600	328	392	2.5	20.7
61964	320	440	56	3	214	395	1300	1600	348	412	2	24.9
61868	340	420	38	2.1	122	227	1200	1500	360	400	1.5	11.6
61872	360	440	38	2.1	163	242	1100	1400	380	420	2	12.2
61876F3	380	480	46	2.1	214	314	1000	1300	405.5	454.6	1.5	19
61980	400	540	65	4	350	580	950	1200	434	506	3	43.6
61980F3	400	540	65	4	350	580	950	1200	434	506	3	39.4
6080F3	400	600	90	5	480	780	900	1100	450	550	4	86.5
6080M	400	600	90	5	475	780	900	1100	450	550	4	87.9
6084M	420	620	90	5	470	790	900	1100	438	602	4.5	92
6088	440	650	94	6	525	880	850	1000	493	597	5	108
61892	460	580	56	3	266	435	900	1100	491	549	2.5	34.3
608/500	500	620	37	2.1	220	445	800	950	510	609	1.5	20
618/500M	500	620	56	3	315	465	800	950	513	607	2.5	37.3
60/500	500	720	100	6	575	1020	750	900	526	694	5	135
618/530MA	530	650	56	3	276	480	750	900	562	618	2.5	42.1