

Designations	Dimensions			Basic load ratings				Speed ratings		Installation dimensions		Weight
轴承代号	基本尺寸			基本额定载荷				极限转速		安装相关尺寸		重量
	d	D	B	r _{smin} Ew.Fw		Cr	C0r	润滑脂	润滑油	d1	D1	
	mm			mm				KN		mm		
NJ2222M	110	200	53	2.1	132	320	470	2800	3400	140	169.6	7.83
NU2324M	120	260	86	3	154	670	970	1900	2400	149.6	214.5	24.2
N2326M	130	230	93	4	243	869	1180	1800	2200	182.2	248.4	29
NU2326M	130	280	93	4	167	869	1180	1800	2200	161.6	230.8	28.7
NJ2326M	130	280	93	4	167	869	1180	1800	2200	180	230.8	29.4
NJ2326M/C3YA8-2	130	280	93	4	167	870	1180	1800	2200	180	230.8	29.4
NU1028	140	210	33	1.1	158	166	263	3000	3600	155.2	186	3.89
NJ228M	140	250	42	3	169	363	490	2000	2600	178.1	212.7	9.38
NJ2330M	150	320	108	4	193	1070	1480	1700	2000	208	263.6	42.4
NJ2330M/C3YA8-1	150	320	108	4	193	1120	1590	1700	2000	208	263.6	42.4
NJ234M	170	310	52	4	208	550	780	1800	2200	204.6	260	19.2
NU1034M/C4	170	260	42	2.1	193	272	400	2200	2800	189.4	229.3	8.23
NU236EM	180	320	52	4	217	615	830	1700	2000	214.6	276	18.7
NJ2336M	180	380	126	4	232	1360	1850	1300	1600	251	308	72
NU1038M	190	290	46	2.1	215	350	600	2000	2600	211.8	257	10.9
NU1040M	200	310	51	2.1	227	468	705	1900	2400	223	273.2	14.3
NU240	200	360	58	4	244	685	995	1500	1800	240.4	304	26.5
NU244M	220	400	65	4	270	835	1220	1500	1800	265.8	337	35
NU1044	220	340	56	3	250	485	810	1800	2200	246.9	300	19.2
N244	220	400	65	4	350	760	1220	1500	1800	284	354.2	36.7
NU1048M	240	360	56	3	270	512	775	1700	2000	267.6	320	20.5
NU2252X2M	260	480	150	5	320	2100	3600	900	1150	310.4	400	128
NU2156X2M/C3YA4-1	280	460	123.825	5	321	1900	3300	900	1150	314.9	398.1	85.5
NU2264X2M-1	320	580	170	5	390	2940	5200	900	1100	382.4	485	212
NU2364/HCR	320	670	200	7.5	410	4590	7200	810	950	397.7	562	349
NU3168E	340	580	190	5	399	3300	5900	760	910	389	506	211
NU3168EF3	340	580	190	5	399	3300	5900	760	910	389	506	211
NU3168WB/C3	340	580	190	5	400	3550	6650	760	910	392	500	213
NU2268MA	340	620	165	6	416	2950	4900	810	950	403.2	520.8	230
NU3272M/HC	360	650	232	6	435	4400	8050	800	950	421.6	552	352
NU3276/HC	380	680	240	6	458	5860	9290	760	850	441.9	580	383
NU3184EM	420	700	224	6	485	4950	8950	650	780	473.8	609	366
NU3188F3	440	720	226	6	508	5130	9820	600	750	500.2	636	374
NU3288X2/HC	440	790	255	7.5	530	5760	10700	400	480	516.1	666	583
NU3192MA	460	760	240	7.5	531	5450	10400	400	480	520.3	665	481
NU2292/HCC3YAD	460	830	212	7.5	554	5700	10000	580	670	541.2	706	505
NU31/500/HCC9YA3	500	830	264	7.5	581	7500	12200	480	580	563.6	721	602
NU12/500X3/HCP6	500	900	210	7.5	600	6500	11800	540	650	587.9	765	606
NU12/500/HCERC9	500	920	185	7.5	605	5800	9800	540	650	592.1	778	572
NU12/500/HCEC9	500	920	185	7.5	605	5800	9800	540	650	592.1	778	572