

Designations		Dimensions				Basic load ratings		Installation dimensions			
轴承代号		基本尺寸				基本额定载荷		安装相关尺寸			
Cylindrical Bore	Taper Bore	d	D	B	r _{min}	Cr	COr	d1	D1	b	k
		mm				KN		mm			
22208C	22208C/W33	40	80	23	1.1	91.7	85.5	50.4	68.9	5.5	2
22310CA	22310CA/W33	50	110	40	2	157	208	69	90.559	-	-
22211CA	22211CA/W33	55	100	25	1.5	119	120	68.8	87.3	5.5	2
22312CA	22312CA/W33	60	130	46	2.1	295	318	81.4	108	-	-
22213CA	22213CA/W33	65	120	31	1.5	183	205	81.5	103	5.5	2.5
22313CA	22313CA/W33	65	140	48	2.1	323	342	88.6	116	5.5	3
22215CA	22215CA/W33	75	130	31	1.5	201	228	92	114	5.5	2.5
22316CA	22316CA/W33	80	170	58	2.1	345	495	109	141.58	-	-
22317CA	22317CA/W33	85	180	60	3	410	505	115	150.479	-	-
22318CA	22318CA/W33	90	190	64	3	420	625	123	158.572	-	-
22319CA	22319CA/W33	95	200	67	3	560	740	127.5	167.07	-	-
22320CA	22320CA/W33	100	215	73	3	540	815	137.7	178.662	-	-
23121CA	23121CA/W33	105	175	56	2	365	550	127	150.95	-	-
23222CA	23222CA/W33	110	200	69.8	2.1	540	720	138	168.083	-	-
22322CA	22322CA/W33	110	240	80	3	630	955	151	197.406	-	-
22224CA	22224CA/W33	120	215	58	2.1	425	680	150.5	187.22	-	-
22324CA	22324CA/W33	120	260	86	3	840	1100	165	215.472	-	-
22226C	-	130	230	64	3	561	803	153.39	200.01	-	-
23028C/W33	-	140	210	53	2	420	715	156.101	187.659	8.3	4.5
22330CA	22330CA/W33	150	320	108	4	1120	1810	203	264.824	16.7	9
22332CA	22332CA/W33	160	340	114	4	1270	2050	216	283.972	-	-
22232C	-	160	290	80	3	860	1280	191.012	249.49	-	-
23134C	-	170	280	88	2.1	910	1520	194.42	242.528	-	-
22234	-	170	310	86	4	890	1370	212	267.516	-	-
22236K	-	180	320	86	4	845	1430	222	276.96	-	-
22236CA	22236CA/W33	180	320	86	4	895	1550	223.5	278.002	-	-
22336CA	22336CA/W33	180	380	126	4	1470	2400	242	315.791	-	-
23036C	-	180	280	74	2.1	730	1290	205.128	247.16	-	-
22238CA	22238/W33	190	340	92	4	865	1620	235	292.89	-	-
23038CA	23038CA/W33	190	290	75	2.1	700	1450	223.6	259.374	-	-
23040	-	200	310	82	2.1	660	1370	236	270.86	-	-
22240C	-	200	360	98	4	1100	1950	237.23	308.8	-	-
22244CA/C3W33	-	220	400	108	4	1350	2400	275	344.47	16.7	9
22344CA	22344CA/W33	220	460	145	5	2370	3450	293.5	384.572	-	-
23048C/W33	-	240	360	92	3	1130	2080	271.595	325	13.9	7.5
24052CA/W33	-	260	400	140	4	1710	3500	300	347	11.1	6
23152CA	23152CA/W33	260	440	144	4	2420	3700	310	379	16.7	9
22252CA	22252CA/W33	260	480	130	5	2520	3370	330	414	22.3	12
23156CA	23156CA/W33	280	460	146	5	2520	4040	333	400	16.7	8
24156CA/HCW33	24156CA/W33	280	460	180	5	2900	4840	327	388	13.9	8
22356CA/W33	22356CA	280	580	175	6	3800	4940	364	485	22.3	8
22356/W33	-	280	580	175	6	3800	5250	372	485	22.3	8
24060CA	24060CA/W33	300	460	160	4	2570	4510	342	399	13.9	7
24160CA	24160CA/W33	300	500	200	5	3560	5990	356	420	13.9	6
23260CA	23260CA/W33T	300	540	192	5	3700	5560	373	455	22	10
23064CA	23064CA/W33	320	480	121	4	2130	3610	368	431	16.7	8
24064CA	24064CA/W33	320	480	160	4	2700	4850	368	421	22	8
24164CA/W33	24164CA/W33T	320	540	210	5	4040	6750	382	457.4	16.7	9
22264CA	22264CA/W33	320	580	150	5	3420	4660	400	502	22.3	8
23264CA	23264CA/W33	320	580	208	5	4180	6370	400	490	24	10
24068CA/W33	24068CA/C9W33	340	520	180	5	3280	5890	394	451	16.7	8
24164CA/W33	24164CA/W33T	340	540	210	5	4040	6750	364	455	16.7	9
23168CA	23168CA/W33	340	580	190	5	4040	6460	412	497	22.3	8
23264CA/C3YA1W33	23264/W33	340	580	208	5	4180	6370	400	490	24	10
24168CA/W33	-	340	580	243	5	5040	8220	408	486	22.3	10
23172CAK/W33	24172CA/W33	360	600	192	5	4080	6600	434	518	22.3	12
24172CA	24172CA/W33	360	600	243	5	5320	8840	430	511	20	12
22372CA/W33	-	360	750	224	7.5	5650	8600	471	631	22.3	-
23076CA	23076CA/W33	380	560	135	5	2750	4750	441	505	22.3	8
23176/W33	-	380	620	194	5	4180	6750	457	540	22	8
23176CA/W33	23176CA/W33T	380	620	194	5	4180	6750	457	540	22	8
23080CA	23080CA/P5W33	400	600	148	5	3090	5420	460	538	22	12
24080CA/W33	-	400	600	200	5	4090	7600	458	524	22	12
23180CA	23180CA/W33	400	650	200	6	4420	7270	480	568	22.3	8
24180CA	24180CA/W33	400	650	250	6	5890	10070	476	563	22.3	8
23280CA	23280CA/W33	400	720	256	6	6220	9880	499	606	22	10
22380CA	22380CA/W33	400	820	243	7.5	7120	9880	520	694	-	-