

型号	主要数据尺寸			基本负荷额定值		疲劳负荷限 值	额定速度		重量
Bearing Designation	Dimension(mm)			Basic load rating			Speed ratings(rpm)		Weight
				动态	静态		参照速度	限制速度	
	d	D	B	C	C0		Pu	Speed Ratings	
	mm			kN		kN	r/min		kg
206	30	62	16	22.9	17.3	0.735	20000	12000	0.21
207	35	72	17	29.7	22.8	0.965	17000	11000	0.31
208	40	80	18	33.6	26.5	1.12	15000	9500	0.39
209	45	85	19	39.6	32.5	1.37	14000	9000	0.44
210	50	90	20	39.1	34.5	1.46	13000	8000	0.5
211	55	100	21	48.4	44	1.86	12000	7500	0.66
212 NR	60	110	22	56.1	50	2.12	11000	6700	0.85
212-2ZNR	60	110	22	56.1	50	2.12	11000	5300	0.85
212-ZNR	60	110	22	56.1	50	2.12	11000	6700	0.85
213 NR	65	120	23	60.5	58.5	2.5	10000	6000	1.05
213-2ZNR	65	120	23	60.5	58.5	2.5	10000	4800	1.05
213-ZNR	65	120	23	60.5	58.5	2.5	10000	6000	1.05
214 NR	70	125	24	66	65.5	2.75	9500	6000	1.15
214-2ZNR	70	125	24	66	65.5	2.75	9500	4500	1.15
214-ZNR	70	125	24	66	65.5	2.75	9500	6000	1.15
215 NR	75	130	25	72.1	72	3	9000	5600	1.25
215-2ZNR	75	130	25	72.1	72	3	9000	4500	1.25
215-ZNR	75	130	25	72.1	72	3	9000	5600	1.25
216 NR	80	140	26	88	85	3.45	8500	5300	1.55
216-2ZNR	80	140	26	88	85	3.45	8500	4000	1.55
216-ZNR	80	140	26	88	85	3.45	8500	5300	1.55
217 NR	85	150	28	96.8	100	3.9	7500	4800	1.95
218 NR	90	160	30	112	114	4.3	7000	4500	2.35
219 NR	95	170	32	121	122	4.5	6700	4300	2.7
206 NR	30	62	16	22.9	17.3	0.735	20000	12000	0.21
206-2ZNR	30	62	16	22.9	17.3	0.735	20000	10000	0.21
206-ZNR	30	62	16	22.9	17.3	0.735	20000	12000	0.21
207 NR	35	72	17	29.7	22.8	0.965	17000	11000	0.31
207-2ZNR	35	72	17	29.7	22.8	0.965	17000	8500	0.31
207-ZNR	35	72	17	29.7	22.8	0.965	17000	11000	0.31
208 NR	40	80	18	33.6	26.5	1.12	15000	9500	0.39
208-2ZNR	40	80	18	33.6	26.5	1.12	15000	7500	0.39
208-ZNR	40	80	18	33.6	26.5	1.12	15000	9500	0.39
209 NR	45	85	19	39.6	32.5	1.37	14000	9000	0.44
209-2ZNR	45	85	19	39.6	32.5	1.37	14000	7000	0.44
209-ZNR	45	85	19	39.6	32.5	1.37	14000	9000	0.44
210 NR	50	90	20	39.1	34.5	1.46	13000	8000	0.5
210-2ZNR	50	90	20	39.1	34.5	1.46	13000	6700	0.5
210-ZNR	50	90	20	39.1	34.5	1.46	13000	8000	0.5
211 NR	55	100	21	48.4	44	1.86	12000	7500	0.66
211-2ZNR	55	100	21	48.4	44	1.86	12000	6000	0.66
211-ZNR	55	100	21	48.4	44	1.86	12000	7500	0.66
206-2Z	30	62	16	22.9	17.3	0.735	20000	10000	0.21
206-Z	30	62	16	22.9	17.3	0.735	20000	12000	0.21
207-2Z	35	72	17	29.7	22.8	0.965	17000	8500	0.31
207-Z	35	72	17	29.7	22.8	0.965	17000	11000	0.31
208-2Z	40	80	18	33.6	26.5	1.12	15000	7500	0.39
208-Z	40	80	18	33.6	26.5	1.12	15000	9500	0.39
209-2Z	45	85	19	39.6	32.5	1.37	14000	7000	0.44
209-Z	45	85	19	39.6	32.5	1.37	14000	9000	0.44
210-2Z	50	90	20	39.1	34.5	1.46	13000	6700	0.5
210-Z	50	90	20	39.1	34.5	1.46	13000	8000	0.5
211-2Z	55	100	21	48.4	44	1.86	12000	6000	0.66
211-Z	55	100	21	48.4	44	1.86	12000	7500	0.66