

Bearing Designation	Dimensions(mm/in)										Ball Diameter	Load Rating	Weight
轴承型号	尺寸(mm/英寸)										钢球直径	载荷(KN)	重量
	d+0.03	B	C1	d2	d3	h1	L3	(L4)	d4	sw			≈ kg
	-0.01				UNF-2B								
F3	4.826	7.92	6.35	15.88	10-32	26.97	11.11	34.91	10.31	7.92	10	7.6	0.018
F3	0.19	0.312	0.25	0.625	10-32	1.062	0.437	1.375	0.406	0.312	10	7.6	0.018
F4	6.35	9.53	7.14	19.05	2001/4/28	33.32	14.28	42.85	11.89	9.52	13	11.3	0.027
F4	0.25	0.375	0.281	0.75	2001/4/28	1.312	0.562	1.687	0.468	0.375	13	11.3	0.027
F5	7.938	11.1	8.74	22.23	5/16-24	34.92	15.88	46.03	12.7	11.1	10	14.5	0.04
F5	0.3125	0.437	0.344	0.875	5/16-24	1.375	0.625	1.812	0.5	0.437	10	14.5	0.04
F6	9.525	12.7	10.31	25.4	2003/8/24	41.28	19.05	53.98	17.45	14.27	9	18.5	0.068
F6	0.375	0.5	0.406	1	2003/8/24	1.625	0.75	2.125	0.687	0.562	9	18.5	0.068
F7	11.112	14.27	11.1	28.58	7/16-20	46.02	22.22	60.3	19.05	15.88	11	22.3	0.09
F7	0.4375	0.562	0.437	1.125	7/16-20	1.812	0.875	2.375	0.75	0.625	11	22.3	0.09
F8	12.7	15.88	12.7	33.32	2001/2/20	53.98	25.4	70.64	22.22	19.05	9	32	0.149
F8	0.5	0.625	0.5	1.312	2001/2/20	2.125	1	2.781	0.875	0.75	9	32	0.149
F10	15.875	19.05	14.27	38.1	2005/8/18	63.5	31.75	82.55	25.4	22.22	11	35.5	0.217
F10	0.625	0.75	0.562	1.5	2005/8/18	2.5	1.25	3.25	1	0.875	11	35.5	0.217
F12	19.05	22.23	17.45	44.45	2003/4/16	73.02	38.1	95.25	28.58	25.4	10	50.2	0.326
F12	0.75	0.875	0.678	1.75	2003/4/16	2.875	1.5	3.75	1.125	1	10	50.2	0.326
F16	25.4	34.93	25.4	69.85	2005/4/12	104.78	53.98	139.7	41.28	38.1	14	164.2	0.963
F16	1	1.375	1	2.75	2005/4/12	4.125	2.125	5.5	1.625	1.5	14	164.2	0.963