

Bearing Designation	Dimensions(mm/in)								Ball Diameter	Load Rating	Weight
轴承	尺寸(mm/英寸)								钢球直径	载荷(KN)	重量
	d+0.03	B	C1	d2	d3	h	L1	(L2)			≈ kg
	-0.01				UNF-2A						
JMX3T	4.826	7.92	6.35	15.88	10-32	31.75	19.05	39.69	11.11	13	0.013
JMX3T	0.19	0.312	0.25	0.625	10-32	1.25	0.75	1.562	0.437	13	0.013
JMX4T	6.35	9.53	7.14	19.05	4/28	39.67	25.4	49.2	12.7	16	0.018
JMX4T	0.25	0.375	0.281	0.75	4/28	1.562	1	1.937	0.5	16	0.018
JMX5T	7.938	11.1	8.74	22.23	5/16	47.63	31.75	58.75	15.88	14	0.031
JMX5T	0.3125	0.437	0.344	0.875	5/16	1.875	1.25	2.312	0.625	14	0.031
JMX6T	9.525	12.7	10.31	25.4	8/24	49.22	31.75	61.92	18.26	12	0.049
JMX6T	0.375	0.5	0.406	1	8/24	1.938	1.25	2.437	0.719	12	0.049
JMX7T	11.112	14.27	11.1	28.58	7/16	53.98	34.93	68.27	20.62	14	0.072
JMX7T	0.4375	0.562	0.437	1.125	7/16	2.125	1.375	2.678	0.812	14	0.072
JMX8T	12.7	15.88	12.7	33.32	2/20	61.92	38.1	78.58	23.8	12	0.113
JMX8T	0.5	0.625	0.5	1.312	2/20	2.438	1.5	3.093	0.937	12	0.113
JMX10T	15.875	19.05	14.27	38.1	8/18	66.68	41.28	85.73	28.58	16	0.172
JMX10T	0.625	0.75	0.562	1.5	8/18	2.625	1.625	3.375	1.125	16	0.172
JMX12T	19.05	22.23	17.45	44.45	4/16	73.02	44.45	95.25	33.33	14	0.272
JMX12T	0.75	0.875	0.678	1.75	4/16	2.875	1.75	3.75	1.312	14	0.272
JMX14T	22.225	22.23	17.45	50.8	8/14	85.73	47.63	111.1	33.33	10	0.408
JMX14T	0.875	0.875	0.687	2	8/14	3.375	1.875	4.375	1.312	10	0.408
JMX16T	25.4	34.93	25.4	69.85	4/12	104.78	53.98	139.7	47.62	14	1.241
JMX16T	1	1.375	1	2.75	4/12	4.125	2.125	5.5	1.875	14	1.241
JMX16-1T	25.4	34.93	25.4	69.85	1/14	104.78	53.98	139.7	47.62	14	1.117
JMX16-1T	1	1.375	1	2.75	1/14	4.125	2.125	5.5	1.875	14	1.117