

Bearing No.	Dimensions(mm/inches)												Ball dia	Load ratings (KN)	Weight
轴承型号	基本尺寸												钢球直径	载荷(KN)	重量
	d2	C1	ds UNF-2B	d4	SW	hi	L3	M	N UNF-2A	s	P	L			≈ kg
CF3TY	15.88	5.94	10-32	10.31	7.92	26.97	11.1	34.91	10-32	11.1	25.8	11/11	22	4.4	0.022
CF3TY	0.625	0.234	10-32	0.406	0.312	1.062	0.437	1.375	10-32	0.437	1.016	7/16	22	4.4	0.022
CF4TY	19.05	6.35	4/28	11.89	9.52	33.32	14.27	42.85	4/28	12.7	26.18	12.7	20	8.2	0.027
CF4TY	0.75	0.25	4/28	0.468	0.375	1.312	0.562	1.687	4/28	0.5	1.031	1/2	20	8.2	0.027
CF5TY	22.23	7.92	5/16	12.7	11.1	34.92	15.88	46.03	5/16	15.06	30.96	15.88	21	10.2	0.048
CF5TY	0.875	0.312	5/16	0.5	0.437	1.375	0.625	1.812	5/16	0.593	1.219	5/8	21	10.2	0.048
CF6TY	25.4	9.11	8/24	17.45	14.27	41.28	19.05	53.98	8/24	20.62	39.67	18.26	23	14	0.077
CF6TY	1	0.359	8/24	0.687	0.562	1.625	0.75	2.125	8/24	0.812	1.562	23/32	23	14	0.077
CF7TY	28.58	10.31	7/16	19.05	15.88	46.02	22.22	60.3	7/16	23.8	44.45	20.62	22	17.6	0.122
CF7TY	1.125	0.406	7/16	0.75	0.625	1.812	0.875	2.375	7/16	0.937	1.75	13/16	22	17.6	0.122
CF8TY	33.33	11.5	2/20	22.22	19.05	53.98	25.4	70.64	2/20	25.4	50.8	23.8	24	23.7	0.181
CF8TY	1.312	0.453	2/20	0.875	0.75	2.125	1	2.781	2/20	1	2	15/16	24	23.7	0.181
CF10TY	38.1	12.3	8/18	25.4	22.22	63.5	31.75	82.55	8/18	34.93	63.5	28.58	26	25.7	0.308
CF10TY	1.5	0.484	8/18	1	0.875	2.5	1.25	3.25	8/18	1.375	2.5	9/8	26	25.7	0.308
CF12TY	44.45	15.06	4/16	28.58	25.4	73.03	38.1	95.25	4/16	41.28	76.2	33.33	23	42.4	0.503
CF12TY	1.75	0.593	4/16	1.125	1	2.875	1.5	3.75	4/16	1.625	3	21/16	23	42.4	0.503