

型号	最大允许扭矩	最大超运转速度 Max. Overrunning speed		阻力矩	孔径尺寸	键槽	A	B	C	D	E	F	Weight
Type	Largest Allowable Torque (N.m)	内圈 Inner Race	外圈 Outer Race	Drag Torque	Bore Size	Keyway							重量(Kg)
	N·m	R/min	r/min	N·m	H7	-	-	-	-	-	-	-	g
TSS 8	6.7	6,000	3,000	0.005	8	2×1.0	8	24	22.2	11.4	0.6	0.6	14
TSS 10	12	4,500	2,300	0.007	10	3×1.4	9	30	27	15.6	0.6	0.6	27
TSS 12	17	4,000	2,000	0.009	12	4×1.8	10	32	29.5	18	0.6	0.6	31
TSS 15	22	3,500	1,800	0.01	15	5×1.2	11	35	32	20.6	0.6	0.6	39
TSS 20	41	2,600	1,300	0.01	20	6×1.6	14	47	40	26.7	0.8	0.8	115
TSS 25	56	2,200	1,100	0.02	25	8×2.0	15	52	45	32	0.8	0.8	140
TSS 30	105	1,800	900	0.03	30	8×2.0	16	62	55	40	0.8	1.0	215
TSS 35	136	1,600	800	0.03	35	10×2.4	17	72	63	45	0.8	1.0	300
TSS 40	296	1,400	700	0.18	40	12×2.2	18	80	72	50	0.8	1.0	425
TSS 45	347	1,300	650	0.21	45	14×2.1	-	-	-	-	-	-	-
TSS 50	403	1,200	600	0.22	50	14×2.1	-	-	-	-	-	-	-
TSS 60	649	910	460	0.33	60	18×2.3	-	-	-	-	-	-	-