

型号	极限速度 Overrunning speeds					楔块空间 Sprag space				夹子数量	插模钉数量	重量 Weight
	Type	TKN ¹⁾ [Nm]	n ^{max2)} [min ⁻¹]	n ^{max3)} [min ⁻¹]	$\phi_a^{+0.08}_{-0.05}$ [mm]	$\phi_c^{\pm 0.013}$ [mm]	[mm]	e _{min} [mm]	ϕd_{min} [mm]			
DC2222G	50	8,600	4,300	22,225	38,885	8.33 ^{±0.075}	10.0	50	17	-	12	0.030
DC2776	95	6,900	3,400	27,762	44,422	8.33 ^{±0.075}	13.5	58	21	-	14	0.055
DC3034	99	6,300	3,100	30,340	47,000	8.33 ^{±0.075}	13.5	62	23	-	14	0.060
DC3175(3C)	127	6,000	3,000	31,750	48,410	8.33 ^{±0.075}	13.5	63	24	3	16	0.060
DC3809A	220	5,000	2,500	38,092	54,752	8.33 ^{±0.075}	16.0	71	29	-	18	0.085
DC4127(3C)	179	4,600	2,300	41,275	57,935	8.33 ^{±0.075}	13.5	75	32	3	18	0.090
DC4445A	290	4,300	2,100	44,450	61,110	8.33 ^{±0.075}	16.0	79	34	-	20	0.095
DC4972(4C)	245	3,800	1,900	49,721	66,381	8.33 ^{±0.075}	13.5	86	38	4	22	0.100
DC5476A	420	3,500	1,700	54,765	71,425	8.33 ^{±0.075}	16.0	92	42	-	24	0.110
DC5476A(4C)	420	3,500	1,700	54,765	71,425	8.33 ^{±0.075}	16.0	92	42	4	24	0.130
DC5476B(4C)	615	3,500	1,700	54,765	71,425	8.33 ^{±0.075}	21.0	92	42	4	24	0.180
DC5476C(4C)	792	3,500	1,700	54,765	71,425	8.33 ^{±0.075}	25.4	92	42	4	24	0.200
DC5776A	483	3,300	1,600	57,760	74,420	8.33 ^{±0.075}	16.0	98	44	-	26	0.110
DC6334B	645	3,000	1,500	63,340	80,000	8.33 ^{±0.075}	21.0	104	50	-	26	0.175
DC7221(5C)	540	2,600	1,300	72,217	88,877	8.33 ^{±0.075}	13.5	115	56	5	30	0.140
DC7221B	1,023	2,600	1,300	72,217	88,877	8.33 ^{±0.075}	21.0	115	56	-	30	0.185
DC7221B(5C)	1,023	2,600	1,300	72,217	88,877	8.33 ^{±0.075}	21.0	115	56	5	30	0.210
DC7969C(5C)	1,630	2,400	1,200	79,698	96,358	8.33 ^{±0.075}	25.4	124	61	5	34	0.280
DC8334C	1,645	2,300	1,100	83,340	100,000	8.33 ^{±0.075}	25.4	132	65	-	34	0.270
DC8729A	1,000	2,200	1,100	87,290	103,960	8.33 ^{±0.075}	16.0	134	67	-	34	0.165
DC10323A(3C)*	1,290	1,800	900	103,231**	119,891	8.33 ^{±0.075}	16.0	155	80	3	40	0.205
DC12334C*	3,840	1,500	750	123,340**	140,000	8.33 ^{±0.075}	25.4	184	96	-	50	0.400
DC12388C(11C)	3,900	1,500	750	123,881	142,880	9.50 ^{±0.10}	25.4	186	96	11	44	0.400

