

Principal dimensions			Basic load ratings (kN)		Pu	Speed ratings		Weight	Designation	Dimensions (mm)										Abutment and fillet dimensions (mm)			Value		
基本尺寸			基本额定负荷			极限	额定转速			重量	型号	尺寸										安装尺寸			计算系数
d _i	D	B	dyc	stc	Speed Ratings		Limiting Speed	(kg)	d			d _i	D1	B	C	C1	r _{1,2}	r _{1,4}	a	d ₁	d ₂	r _a	e	Y	Y ₀
(mm)			Cr	Cor	(rpm)									Min	Min		Max	Min	Max						
40	68	19	60	71	7.65	7500	9500	0.27	32008XR/CVA821	40	54.2	72	19	14.5	3.5	1	1	15	46	46	1	0.37	1.6	0.9	
40	80	19.75	71	88	7.85	7000	9500	0.42	30208RJZ/Q	40	57.5	85	18	16	4	1.5	1.5	16	49	47	1	0.37	1.6	0.9	
45	85	32	108	143	16.3	6300	7500	0.85	33208RJ/Q	45	65.2	90	32	25	5	1.5	1.5	22	52	52	1	0.4	1.5	0.8	
45	100	38.25	156	176	20	5000	6700	1.50	32308BRJ/QCL7C	45	74.8	106	36	30	7	2	1.5	30	55	54	1.5	0.54	1.1	0.6	
55	120	45.5	216	260	30	4300	5600	2.50	32311BRJ/QCL7C	55	90.5	127	43	35	8	2.5	2	36	67	65	2	0.54	1.1	0.6	
65	110	34	142	208	24	4300	5600	1.30	33113RJ/Q	65	87.9	116	34	28.5	5.5	1.5	1.5	26	74	72	1	0.4	1.5	0.8	
65	140	35	194	228	27.5	3600	4800	2.40	30313RJ2	65	98.3	147	33	28	6	3	2.5	28	84	77	2	0.35	1.7	0.9	
65	140	35	194	228	27.5	3600	4800	2.40	30313RJ2	65	98.3	147	33	28	6	3	2.5	28	84	77	2	0.35	1.7	0.9	