

Designation	Mass ≈g	Designation	Mass ≈g	尺寸(毫米) Dimensions(mm)						基本额定负荷 Basic load ratings(N)		Fatigue limit load C <sub>urw</sub> N	Speed n <sub>DG</sub> min <sup>-1</sup>
型号	质量 (克)	型号	质量 (克)	D	d	B	C	d <sub>2</sub>	r min.	dyn. C <sub>r,w</sub> 动态	stat. C <sub>or,w</sub> 静态	极限疲劳 载荷	极限转速
NATR5	14	NATR5-PP	14	16	5	12	11	12.5	0.15	3150	3300	415	14000
NATV5	15	NATV5-PP	15	16	5	12	11	12.5	0.15	4900	6500	860	3800
NATR6	20	NATR6-PP	19	19	6	12	11	15	0.15	3500	3900	485	11000
NATV6	21	NATV6-PP	21	19	6	12	11	15	0.15	5400	7900	1040	3100
NATR8	41	NATR8-PP	38	24	8	15	14	19	0.3	5500	6400	810	7500
NATV8	42	NATV8-PP	41	24	8	15	14	19	0.3	7800	11400	1430	2500
NATR10	64	NATR10-PP	61	30	10	15	14	23	0.6	6800	8400	1070	5500
NATV10	65	NATV10-PP	64	30	10	15	14	23	0.6	9500	14600	1840	2100
NATR12	71	NATR12-PP	66	32	12	15	14	25	0.6	6900	8800	1720	4500
NATV12	72	NATV12-PP	69	32	12	15	14	25	0.6	9700	15400	1950	1800
NATR15	104	NATR15-PP	95	35	15	19	18	27.6	0.6	9800	14100	1700	3600
NATV15	109	NATV15-PP	101	35	15	19	18	27.6	0.6	12800	23000	2900	1600
NATR17	144	NATR17-PP	139	40	17	21	20	31.5	1	10900	15500	1850	2900
NATV17	152	NATV17-PP	147	40	17	21	20	31.5	1	14800	26500	3050	1400
NATR20	246	NATR20-PP	236	47	20	25	24	36.5	1	15500	25500	3000	2400
NATV20	254	NATV20-PP	245	47	20	25	24	36.5	1	20600	42000	5200	1300
NATR25	275	NATR25-PP	271	52	25	25	24	41.5	1	15400	26500	3010	1800
NATV25	285	NATV25-PP	281	52	25	25	24	41.5	1	20500	44000	5400	1000
NATR30	470	NATR30-PP	444	62	30	29	28	51	1	23400	38500	4650	1300
NATV30	481	NATV30-PP	468	62	30	29	28	51	1	30500	62000	7800	850
NATR35	-	NATR35-PP	547	72	35	29	28	58	1.1	25000	44000	5300	1000
NATV35	-	NATV35-PP	630	72	35	29	28	58	1.1	33000	71000	8900	750
NATR40	-	NATR40-PP	795	80	40	32	30	66	1.1	32500	58000	7000	850
NATV40	-	NATV40-PP	832	80	40	32	30	66	1.1	41000	88000	11000	650
NATR50	-	NATR50-PP	867	90	50	32	30	76	1.1	31500	59000	7100	650
NATV50	-	NATV50-PP	969	90	50	32	30	76	1.1	40000	92000	11600	550