

Bearing Designation	Mass g	With eccentric collar Designation	尺寸(毫米) Dimensions														Eccentric collar			Drive fit lubrication nipple	Nut tightening torque	基本额定负荷 Basic load ratings				Fatigue limit load C ₁₀ = N	Speed n ₃ min ⁻¹
			D	d ₁ h ₇	B	B ₁ max.	B ₂	B ₃	C	C ₁	r min.	d ₂	d ₃	G	IG	W	偏心套	油嘴	螺母拧紧扭矩			d _{yn} C ₁₀ 动态	stat. C ₀	d _{yn} F _{r per}	stat. F _{r per}		
轴承型号	质量 (克)	带偏心套型号	(mm)														d _e	B _e	e	(N)							
NUKR35	164	-	-	35	16	52	19.6	32.5	7.8	18	0.8	0.6	20	3	M16×1.5	17	8	-	-	-	58	15000	16800	8600	16800	2220	6500
-	-	NUKRE35	177	35	16	52	22.6	29.5	-	18	3.8	0.6	27.6	-	M16×1.5	17	8	20	12	1	58	15000	16800	8600	16800	2220	6500
PWKR35-2RS	164	-	-	35	16	52	19.6	32.5	7.8	18	0.8	0.6	20	3	M16×1.5	17	8	-	-	-	58	11600	11300	9400	11300	1780	6000
-	-	PWKRE35-2RS	177	35	16	52	22.6	29.5	-	18	3.8	0.6	27.6	-	M16×1.5	17	8	20	12	1	58	11600	11300	9400	11300	1780	6000
NUKR40	242	-	-	40	18	58	21.6	36.5	8	20	0.8	1	22	3	M18×1.5	19	8	-	-	-	87	18400	22600	13100	22600	2900	5500
-	-	NUKRE40	258	40	18	58	24.6	33.5	-	20	3.8	1	30	-	M18×1.5	19	8	22	14	1	87	18400	22600	13100	22600	2900	5500
PWKR40-2RS	242	-	-	40	18	58	21.6	36.5	8	20	0.8	1	22	3	M18×1.5	19	8	-	-	-	87	13200	13800	13800	13800	2200	5000
-	-	PWKRE40-2RS	258	40	18	58	24.6	33.5	-	20	3.8	1	30	-	M18×1.5	19	8	22	14	1	87	13200	13800	13800	13800	2200	5000
NUKR47	380	NUKRE47	400	47	20	66	25.6	40.5	9	24	0.8	1	27	4	M20×1.5	21	10	24	18	1	120	28000	35000	33000	33000	4400	4200
PWKR47-2RS	380	PWKRE47-2RS	400	47	20	66	25.6	40.5	9	24	0.8	1	27	4	M20×1.5	21	10	24	18	1	120	23200	25500	25500	25500	3600	3800
NUKR52	450	NUKRE52	470	52	20	66	25.6	40.5	9	24	0.8	1	31	4	M20×1.5	21	10	24	18	1	120	29000	37500	34500	34500	4700	4200
PWKR52-2RS	450	PWKRE52-2RS	470	52	20	66	25.6	40.5	9	24	0.8	1	31	4	M20×1.5	21	10	24	18	1	120	24200	28000	28000	28000	3900	3800
NUKR62	795	NUKRE62	824	62	24	80	30.6	49.5	11	28	1.3	1	38	4	M24×1.5	25	14	28	22	1	220	40000	50000	46500	46500	6300	2600
PWKR62-2RS	795	PWKRE62-2RS	824	62	24	80	30.6	49.5	11	28	1.3	1	38	4	M24×1.5	25	14	28	22	1	220	35000	39500	39500	39500	5400	2200
NUKR72	1020	NUKRE72	1050	72	24	80	30.6	49.5	11	28	1.3	1.1	44	4	M24×1.5	25	14	28	22	1	220	44500	60000	60000	60000	7600	2600
PWKR72-2RS	1020	PWKRE72-2RS	1050	72	24	80	30.6	49.5	11	28	1.3	1.1	44	4	M24×1.5	25	14	28	22	1	220	38500	46500	46500	46500	6300	2200
NUKR90	1960	NUKRE90	1670	80	30	100	37	63	15	35	1	1.1	47	4	M30×1.5	32	14	35	29	1.5	450	69000	96000	96000	96000	12100	1800
PWKR90-2RS	1600	PWKRE90-2RS	1670	80	30	100	37	63	15	35	1	1.1	47	4	M30×1.5	32	14	35	29	1.5	450	56000	70000	70000	70000	9100	1800
NUKR90	1960	NUKRE90	2020	90	30	100	37	63	15	35	1	1.1	47	4	M30×1.5	32	14	35	29	1.5	450	79000	117000	117000	11700	14400	1800
PWKR90-2RS	1960	PWKRE90-2RS	2020	90	30	100	37	63	15	35	1	1.1	47	4	M30×1.5	32	14	35	29	1.5	450	63000	82000	82000	82000	10700	1800