

Designation (With inner ring)	Mass ≈g	尺寸(毫米) Dimensions(mm)								基本额定负荷 Basic load ratings(N)		Fatigue limit load C _{urw}	Limit speed n _{DG} min ⁻¹
型号(有内圈)	质量 (克)	D	d	C	B	F ¹⁾ F _w	D ₁	r	r ₁	dyn. C _{r w} 动态	stat. C _{or w} 静态	极限疲劳载荷 (N)	极限转速
NA22/6-2RSR	22	19	6	11.8	12	10	16	0.3	0.3	3900	3650	520	9000
NA22/8-2RSR	34	24	8	11.8	12	12	18	0.3	0.3	4800	4800	860	7000
NA2200-2RSR	60	30	10	13.8	14	14	20	0.6	0.3	7000	8000	1170	5500
NA2201-2RSR	67	32	12	13.8	14	16	22	0.6	0.3	7500	9000	1030	4700
NA2202-2RSR	75	35	15	13.8	14	20	26	0.6	0.3	7600	9500	1380	3400
NA2203-2RSR	112	40	17	15.8	16	22	28	1	0.3	9900	13700	1870	3000
NA2204-2RSR	177	47	20	17.8	18	25	33	1	0.3	15200	18300	2600	2300
NA2205-2RSR	209	52	25	17.8	18	30	38	1	0.3	15700	19900	2850	1800
NA2206-2RSR	324	62	30	19.8	20	35	43	1	0.3	18400	25500	3300	1400
NA2207-2RSR	505	72	35	22.7	23	42	50	1.1	0.6	23000	35500	4800	1100
NA2208-2RSR	628	80	40	22.7	23	48	57	1.1	0.6	27500	40500	5000	850
NA2210-2RSR	690	90	50	22.7	23	58	68	1.1	0.6	28000	42500	5300	650