

Bearing Designation	Dimensions(mm)													Automatic self-aligning Angle	Jackscrew	Weight	Load Rating	
	尺寸(mm)																自动调心角度	顶丝
轴承	d	B	dk	C1	d2	G-6H	h1	l3	l4	l7	d4	de	b					
SQ5-RS	9	19	M5	29	8	10	21	7	35	27	14	9	11	16	9	25	2.2	0.026
SQ6-RS	10	20	M6	35.5	11	11	26	8	40	30	14	10	13	19	11	25	3.5	0.039
SQ8-RS	12	24	M8	42.5	12	14	31	10	48	36	17	12.5	16	23	14	25	6.6	0.068
SQ10-RS	14	30	M10X1.25	50.5	15	17	37	11	57	43	21	15	19	27	17	25	10	0.112
SQ12-RS	17	32	M12x1.25	57.5	17	19	42	15	66	50	25	17.5	22	31	19	25	16	0.164
SQ14-RS	19	38	M14X1.5	73.5	22	21.5	56	17	75	57	26	20	25	35	22	25	19	0.254
SQ16-RS	22	44	M16X1.5	79.5	23	23.5	60	19	84	64	32	22	27	39	22	20	26	0.336
SQ18-RS	23	45	M18x1.5	90	25	26.5	68	20	93	71	34	25	31	44	27	20	33	0.464
SQ20-RS	27	50	M20X1.5	90	25	27	68	24	99	77	35	27.5	34	44	30	20	45	0.538
SQ22-RS	27	52	M22X1.5	95	26	28	70	24	109	84	41	30	37	50	32	16	48	0.713