

型号		英制尺寸									径向静载荷 (磅)	约重 (磅)
Designation		Dimensions in inches									Radial Static load Capacity (pounds)	Approx Weight (pounds)
左旋	右旋	B	W	H	A	D	球径	C	线型	α		
Left Hand	Right Hand						Ball Diameter		Thread size			
MSM3	MSML3	0.19	0.312	0.234	1.25	0.625	0.437	0.75	10-32	17	1.17	0.03
MSM4	MSML4	0.25	0.375	0.25	1.562	0.75	0.5	1	1/4-28	21	2.157	0.04
MSM5	MSML5	0.3125	0.437	0.312	1.857	0.875	0.625	1.25	5/16-24	17	3.469	0.07
MSM6	MSML6	0.375	0.5	0.359	1.938	1	0.719	1.25	3/8-24	19	4.916	0.11
MSM7	MSML7	0.4375	0.562	0.406	2.125	1.125	0.812	1.375	7/16-20	18	6.162	0.15
MSM8	MSML8	0.5	0.625	0.453	2.438	1.312	0.937	1.5	1/2-20	17	8.075	0.24
MSM10	MSML10	0.625	0.75	0.484	2.625	1.5	1.125	1.625	5/8-18	22	9.509	0.36
MSM12	MSML12	0.75	0.875	0.593	2.875	1.75	1.312	1.75	3/4-16	18	13.831	0.57
MSM3	MSML3	4.83	7.92	5.94	31.75	15.88	11.1	19.05	10-32	17	0.531	14
MSM4	MSML4	6.35	9.53	6.35	39.67	19.05	12.7	25.4	1/4-28	21	0.978	18
MSM5	MSML5	7.94	11.1	7.92	47.63	22.23	15.88	31.75	5/16-24	17	1.574	32
MSM6	MSML6	9.53	12.7	9.12	49.23	25.4	18.26	31.75	3/8-24	19	2.23	50
MSM7	MSML7	11.11	14.27	10.31	53.98	28.58	20.62	34.93	7/16-20	18	2.795	68
MSM8	MSML8	12.7	15.88	11.5	61.93	33.32	23.8	38.1	1/2-20	17	3.663	109
MSM10	MSML10	15.88	19.05	12.29	66.68	38.1	28.58	41.28	5/8-18	22	4.313	163
MSM12	MSML12	19.05	22.23	15.06	73.03	44.45	44.45	44.45	3/4-16	18	6.274	259