

型号 Designation	尺寸 Dimensions (mm)														英制 球径	负荷KN	
	d	S	D	B	B1	d1	L	I	L1	L2	W	D1	D2	r	ball dis. inch (mm)	Load Ratings	
																动 C	静 CO
PHSB3 PHSB3EC	.1900 4.826	3/16	.625 15.88	.250 6.35	.312 7.92	.306 7.77	1.375 34.93	.187 4.75	1.062 26.97	.562 14.27	.312 7.92	.312 7.92	.406 10.31	.012 0.3	7/16 11.112	780	2090
PHSB4 PHSB4EC	.2500 6.350	1/4	.750 19.05	.281 7.14	.375 9.53	.355 9.02	1.687 42.85	.187 4.75	1.312 33.32	.750 19.05	.375 9.53	.375 9.53	.468 11.89	0.020 0.5	33/64 13.097	1030	3040
PHSB5 PHSB5EC	.3125 7.938	5/16	.875 22.23	.344 8.74	.437 11.10	.447 11.35	1.812 46.02	.187 4.75	1.375 34.93	.750 19.05	.437 11.10	.437 11.10	.500 12.70	0.020 0.5	5/8 15.875	1530	3800
PHSB6 PHSB6EC	.3750 9.525	3/8	1.000 25.4	.406 10.31	.500 12.70	.517 13.13	2.125 53.98	.250 6.35	1.625 41.28	.937 23.80	.562 14.27	.562 14.27	.687 17.45	0.020 0.5	23/32 18.256	2080	4980
PHSB7 PHSB7EC	.4375 11.112	7/16	1.125 28.58	.437 11.10	.562 14.27	.586 14.88	2.375 60.33	.250 6.35	1.812 46.02	1.062 26.97	.625 15.88	.625 15.88	.750 19.05	0.020 0.5	13/16 20.638	2520	6020
PHSB8 PHSB8EC	.5000 12.700	1/2	1.312 33.32	.500 12.70	.625 15.88	.698 17.73	2.781 70.64	.250 6.35	2.125 53.98	1.187 30.15	.750 19.05	.750 19.05	.875 22.23	0.020 0.5	15/16 23.812	3330	8370
PHSB10 PHSB10EC	.6250 15.875	5/8	1.500 38.10	.562 14.27	.750 19.05	.839 21.31	3.250 82.55	.312 7.92	2.500 63.50	1.500 38.10	.875 22.23	.875 22.23	1.000 25.40	0.020 0.5	1 1/8 28.575	4500	9050
PHSB12 PHSB12EC	.7500 19.050	3/4	1.750 44.45	.687 17.45	.875 22.23	.978 24.84	3.750 95.25	.312 7.92	2.875 73.03	1.750 44.45	1.000 25.40	1.000 25.40	1.125 28.58	0.020 0.5	1 5/16 33.338	6410	12700
PHSB14 PHSB14EC	.875 22.225	7/8	1.970 50.05	.778 19.75	1.102 28	1.015 25.8	4.29 109	.47 12.00	3.307 84	1.69 43	1.26 32	1.26 32	1.46 37	0.020 0.5	1 1/2 38.1	11200	16800
PHSB16 PHSB16EC	1.0000 25.400	1/2	2.750 69.85	1.000 25.40	1.375 34.93	1.269 32.23	5.500 139.70	.436 11.07	4.125 104.78	2.125 53.98	1.500 38.10	1.500 38.10	1.750 44.45	0.020 0.5	1 7/8 47.625	13300	19500