

型号 Designation	尺寸 Dimensions (mm)														负荷KN Load Ratings		重量 Weight
	d	d3	W	B	C1 max	h1	D2 max	I4 max	I5 max	d4 max	d5 max	dk	I3 min	α-≈	动 C	静 CO	kg
	SI5T/K	5	M5	9	8	6	27	18	36	4	8.5	12	11.11	8	13	3.25	5.7
SI6T/K	6	M6	11	9	6.75	30	20	40	5	10	13	12.7	9	13	4.3	7.2	0.022
SI8T/K	8	M8	14	12	9	36	24	48	5	12.5	16	15.875	12	14	7.2	11.6	0.047
SI10T/K	10	M10	17	14	10.5	43	28	57	6.5	15	19	19.05	15	13	10	14.5	0.077
SI12T/K	12	M12	19	16	12	50	32	66	6.5	17.5	22	22.225	18	13	13.4	17	0.1
SI14T/K	14	M14	22	19	13.5	57	36	75	8	20	26	25.4	21	16	17	24	0.16
SI16T/K	16	M16	24	21	15	64	40	84	8	22	28	28.575	24	15	21.6	28.5	0.22
SI18T/K	18	M18	27	23	16.5	71	44	93	10	25	31	31.7	27	15	26	42.5	0.32
SI20T/K	20	M20	30	25	18	77	48	101	10	27.5	35	34.925	30	14	31.5	42.5	0.42
SI22T/K	22	M22	32	28	20	84	54	111	12	30	38	38.1	32	15	38	57	0.54
SI25T/K	25	M24	36	31	22	94	60	124	12	33.5	42	42.85	36	15	47.5	68	0.72
SI28T/K	28	M27	41	35	24	103	66	136	14	37	46	47.6	41	15	55	75.5	0.82
SI30T/K	30	M30	46	37	25	110	70	145	15	40	50	50.8	45	17	64	88	1.1