

型号	额定扭矩	最大容许误差			最高转速 [min-	扭转弹性 常数	轴向弹性 常数	转动惯量	质量 [kg]	D	L	d1 . d2	N1.N2	LF	LP	S	d3	K	H	M	M1	M2
Designation	Rated torque	偏心 Eccentricity [mm]	偏角 Deflection [°]	轴向位移 Axial displacement [mm]	Max rotating speed	Torsional elasticity constant	Axial elastic constant	Rotational inertia	Weight													
LC-BM-090DS	200	0.3	1 (单膜片)	±1.2	15000	70000	160	2.43x10-3	2.08	90	93.4	32 . 35	78	34	16.6	1.1	50	50	3-6.8	M8	6-M6	3-M6
LC-BM-100DS	300	0.31	1 (单膜片)	±1.4	15000	80000	180	4.39x10-3	2.56	100	94	50 . 52	93	34	17	1	60	58	3-6.8	M8	6-M6	3-M6
LC-BM-120DS	500	0.38	1 (单膜片)	±1.6	15000	70000	180	8.74x10-3	3.76	120	104.4	55	98	36	21.2	1	72	68	3-8.6	M10	6-M6	3-M6
LC-BM-140DS	800	0.44	1 (单膜片)	±2.0	15000	50000	180	21.5x10-3	6.77	140	126.2	60 . 62	115	45	24.6	1	80	78	3-8.6	M12	6-M8	3-M8