

Bearing Designation	Dimensions(mm/inch)						Static Radial Load (pounds)		Weight
轴承型号	尺寸(mm/inch)						静态径向载荷 (磅)		重量
	d +0.038	D +0	B ±0.127	C±0.127	dk	rsx45°	MIB-T	AIB-T/SIB-T	≈Kg
	-0.012	-0.016							
COM3	0.19	0.5625	0.281	0.281	0.406	0.02	11	21.6	0.0045
COM4	0.25	0.6562	0.343	0.25	0.5	0.022	13.5	33	0.009
COM5	0.3125	0.75	0.375	0.281	0.562	0.032	12	43.2	0.0136
COM6	0.375	0.8125	0.406	0.312	0.656	0.032	10	56	0.018
COM7	0.4375	0.9062	0.437	0.434	0.718	0.032	8	63	0.022
COM8	0.5	1	0.5	0.39	0.813	0.032	9.5	88.4	0.031
COM9	0.5625	1.0937	0.562	0.437	0.906	0.032	9.5	110.9	0.04
COM10	0.625	1.1875	0.625	0.5	1	0.032	8.5	141.9	0.049
COM12	0.75	1.4375	0.75	0.593	1.187	0.044	9	212.98	0.09
COM14	0.875	1.5625	0.875	0.703	1.312	0.044	9.5	279.9	0.118
COM16	1	1.75	1	0.797	1.5	0.044	10	368.3	0.177