

型号	额定扭矩	最大容许误差			最高转速	扭转弹性 常数	轴向弹性 常数	转动惯量	质量 [kg]	d1 . d2			D	N	L	LF	S	F	K	M
Designation	Rated torque	偏心 Eccentricity [mm]	偏角 Deflection [°]	轴向位移 Axial displacement [mm]	Max rotating speed	Torsional elasticity constant	Axial elastic constant	Rotational inertia	Weight	底孔 bottom hole	最小 min	最大 max								
LC-BH-150S	1000	-	1	±0.4	5900	1500000	244	12.48x10-3	4.66	20	22	70	152	104	101	45	11	5	94	6-M8x36
LC-BH-170S	1300	-	1	±0.5	5100	2840000	224	26.88x10-3	7.49	25	28	80	178	118	124	55	14	6	108	6-M10x45
LC-BH-190S	2000	-	1	±0.5	4700	3400000	244	43.53x10-3	10.49	30	32	85	190	126	145	65	15	10	116	6-M12x54
LC-BH-210S	4000	-	1	±0.55	4300	4680000	508	67.87x10-3	13.65	35	38	90	210	130	165	75	15	8	124	6-M16x60
LC-BH-220S	5000	-	1	±0.6	4000	5940000	448	101.70x10-3	18.1	45	48	100	225	144	200	90	20	-2	132	6-M16x60
LC-BH-260S	8000	-	1	±0.7	3400	10780000	612	232.54x10-3	29.46	50	55	115	262	166	223	100	23	11	150	6-M20x80