

型号 Designation	额定扭矩 [N·m]		最大允许误差			最高转速 [min <sup>-1</sup> ] Max rotating speed	转动惯量 [kg·m <sup>2</sup> ] Rotational inertia	扭转弹性常数 Torsional elasticity constant	质量 [kg] Weight	轴径		φD	L	W	L1	L2	M	拧紧扭矩 [N·m]
	min	max	偏心 Eccentricity [mm]	俯角 Deflection [°]	轴向位移 Axial displacement [mm]					Shaft diameter								Seating Torque
										d1	d2							
LC-BK-068SS	55	110	0.02	1	±1.0	4500	0.39×10 <sup>-3</sup>	31×10 <sup>3</sup>	1	11-12-14-15-16	68	90	7	41.5	26	4-M5	4	
LC-BK-082SS	80	160	0.02	1	±1.0	4500	0.96×10 <sup>-3</sup>	89×10 <sup>3</sup>	1.554	14-15-16-19-20	82	95	7	44	26	4-M6	7	
LC-BK-094SS	150	300	0.02	1	±1.0	4500	1.85×10 <sup>-3</sup>	180×10 <sup>3</sup>	2.432	19-20-22-24	94	110	8	51	29	4-M6	7	
LC-BK-104SS	220	440	0.02	1	±1.0	4500	2.96×10 <sup>-3</sup>	265×10 <sup>3</sup>	3.05	24-25-28-30	104	124	10	57	34	6-M6	7	
LC-BK-126SS	350	700	0.02	1	±1.0	4500	7.1×10 <sup>-3</sup>	450×10 <sup>3</sup>	6.524	30-35-38-40	126	152	11	70.5	42	4-M8	15	
LC-BK-144SS	500	1000	0.02	1	±1.0	4500	14.3×10 <sup>-3</sup>	790×10 <sup>3</sup>	8.739	35-38-40-42-45	144	170	12	79	48	6-M8	15	