

型号	额定扭矩 [N・m]		最大容许误差			最高转速	转动惯量	扭转弹性 常数	质量 [kg]	轴径	φD	L	W	L1	L2	L3	M	锁紧扭矩
Designation	Rated torque		偏心	偏角	轴向位移	Max rotating speed	Rotational inertia	Torsional elasticity constant	Weight	Shaft diameter								Seating Torque
	min	max	Eccentricity [mm]	Deflection [°]	Axial displacement [mm]					d1 . d2								
LC-BK-068DS	55	110	0.04	2	±1.5	4500	0.71×10-3	15×103	1.465	11·12·14·15·16	68	121	7	41.5	26	24	4-M5	4
LC-BK-082DS	80	160	0.04	2	±1.5	4500	1.85×10-3	44×103	2.116	14·15·16·19·20	82	128	7	44	26	26	4-M6	7
LC-BK-094DS	150	300	0.04	2	±1.5	4500	3.62×10-3	90×103	3.605	19·20·22·24	94	148	8	51	29	30	4-M6	7
LC-BK-104DS	220	440	0.04	2	±1.5	4500	5.8×10-3	130×103	5.239	24·25·28·30	104	164	10	57	34	30	6-M6	7
LC-BK-126DS	350	700	0.04	2	±1.5	4500	13.1×10-3	220×103	9.399	30·35·38·40	126	201	11	70.5	42	38	4-M8	15
LC-BK-144DS	500	1000	0.04	2	±1.5	4500	26.5×10-3	380×103	13.033	35·38·40·42·45	144	228	12	79	48	46	6-M8	15