

轴承型号	主要尺寸					轴肩尺寸		额定负荷		重量
Designation	Dimensions (mm)					Shoulder size		Basic Load ratings (KN)		Weight
	d(mm)	D(mm)	Dpw(mm)	B/B1	r(min)	ds	Dh	Cr	Cor	kg
RB2008	20	36	27	8	0.5	23.5	30.5	3.23	3.1	0.04
RB2508	25	41	32	8	0.5	28.5	35.5	3.63	3.83	0.05
RB3010	30	55	41.5	10	0.6	37	47	7.35	8.36	0.12
RB3510	35	60	46.5	10	0.6	41	51.5	7.64	9.12	0.13
RB4010	40	65	51.5	10	0.6	47.5	57.5	8.33	10.6	0.16
RB4510	45	70	56.5	10	0.6	51	61.5	8.62	11.3	0.17
RB5013	50	80	64	13	0.6	57.4	72	16.7	20.9	0.27
RB6013	60	90	74	13	0.6	68	82	18	24.3	0.3
RB7013	70	100	84	13	0.6	78	92	19.4	27.7	0.35
RB8016	80	120	98	16	0.6	91	111	30.1	42.1	0.7
RB9016	90	130	108	16	1	98	118	31.4	45.3	0.75
RB10016	100	140	119.3	16	1	109	129	31.7	48.6	0.83
RB10020	100	150	123	20	1	113	133	33.1	50.9	1.45
RB11012	110	135	121.8	12	0.6	117	127	12.5	24.1	0.4
RB11015	110	145	126.5	15	0.6	122	136	23.7	41.5	0.75
RB11020	110	160	133	20	1	120	143	34	54	1.56
RB12016	120	150	134.2	16	0.6	127	141	24.2	43.2	0.72
RB12025	120	180	148.7	25	1.5	133	164	66.9	100	2.62
RB13015	130	160	144.5	15	0.6	137	152	25	46.7	0.72
RB13025	130	190	158	25	1.5	143	174	69.5	107	2.82
RB14016	140	175	154.8	16	1	147	162	25.9	50.1	1
RB14025	140	200	168	25	1.5	154	185	74.8	121	2.96
RB15013	150	180	164	13	0.6	157	172	27	53.5	0.68
RB15025	150	210	178	25	1.5	164	194	76.8	128	3.16
RB15030	150	230	188	30	1.5	173	211	100	156	5.3
RB16025	160	220	188.6	25	1.5	173	204	81.7	135	3.14
RB17020	170	220	191	20	1.5	184	198	29	62.1	2.21
RB18025	180	240	210	25	1.5	195	225	84	143	3.44
RB19025	190	240	211.9	25	1	202	222	41.7	82.9	2.99
RB20025	200	260	230	25	2	215	245	84.2	157	4
RB20030	200	280	240	30	2	221	258	114	200	6.7
RB20035	200	295	247.7	35	2	225	270	151	252	9.6
RB22025	220	280	250.1	25	2	235	265	92.3	171	4.1
RB24025	240	300	269	25	2.5	256	281	68.3	145	4.5
RB25025	250	310	277.5	25	2.5	265	290	69.3	150	5
RB25030	250	330	287.5	30	2.5	269	306	126	244	8.1
RB25040	250	355	300.7	40	2.5	275	326	195	348	14.8
RB30025	300	360	328	25	2.5	315	340	76.3	178	5.9
RB30035	300	395	345	35	2.5	322	368	183	367	13.4
RB30040	300	405	351.6	40	2.5	326	377	212	409	17.2
RB35020	350	400	373.4	20	2.5	363	383	54.1	143	3.9
RB40035	400	480	440.3	35	2.5	422	459	156	370	14.5
RB40040	400	510	453.4	40	2.5	428	479	241	531	23.5
RB45025	450	500	474	25	1	464	484	61.7	182	6.6
RB50025	500	550	524.2	25	1	514	534	65.5	201	7.3
RB50040	500	600	548.8	40	2.5	526	572	239	607	26
RB50050	500	625	561.6	50	2.5	536	587	267	653	41.7
RB60040	600	700	650	40	3	627	673	264	721	29
RB70045	700	815	753.5	45	3	731	777	281	836	46
RB80070	800	950	868.1	70	4	836	900	468	1330	105
RB90070	900	1050	969	70	4	937	1001	494	1490	120