

轴承型号 Designation	外形尺寸 Dimensions (mm)													额定负荷 Basic Load ratings		重量 Weight	
	d	D	B	D1	D2	n1	n2	d1	d11	t1	d2	d21	t2	rsmn	Cr	Cor	kg
RU42	20	70	12	57	28	6	6	3.4	6.5	3.3	M3	—	—	0.6	7.35	8.35	0.29
RU66	35	95	15	83	45	8	8	4.5	8	4.4	M4	—	—	0.6	17.5	22.3	0.62
RU85	55	120	15	105	65	8	8	5.5	9.5	5.4	M5	—	—	0.6	20.3	29.5	1
RU124(G)	80	165	22	148	97	10	10	5.5	9.5	5.4	5.5	9.5	5.4	1	33.1	50.9	2.6
RU124X	80	165	22	148	97	10	10	5.5	9.5	5.4	M5	—	—	1	33.1	50.9	2.6
RU148(G)	90	210	25	187	112	12	12	9	14	8.6	9	14	8.6	1.5	49.1	76.8	4.9
RU148X	90	210	25	187	112	12	12	9	14	8.6	M8	—	—	1.5	49.1	76.8	4.9
RU178(G)	115	240	28	217	139	12	12	9	14	8.6	9	14	8.6	1.5	80.3	135	6.8
RUI78X	115	240	28	217	139	12	12	9	18	8.6	M8	—	—	1.5	80.3	135	6.8
RU228(G)	160	295	35	270	184	12	12	11	18	11	11	18	11	2	104	173	11.4
RU228X	160	295	35	270	184	12	12	11	18	11	M10	—	—	2	10.1	173	11.4
RU297(G)	210	380	40	350	240	16	16	14	20	13	14	20	13	2.5	156	281	21.3
RU297X	210	380	40	350	240	16	16	14	20	13	M12	—	—	2.5	156	281	21.3
RU445(G)	350	540	45	505	385	24	24	14	20	13	14	20	13	2.5	222	473	35.4
RU445X	350	540	45	505	385	24	24	14	20	13	M12	—	—	2.5	222	473	35.4