

Bearing Designation	Dimensions							Limited static radial load (pounds)	Limited static axial load (pounds)	Dynamic swing radial torque (pounds)	Weight
	B	D	T	E	O	REF	a°				
	0	0	±.005	0	REF	REF					
型号	-0.0005	0.0005		-0.01	"V"槽直径	球头端面直径	球径	极限静态径向载荷(磅)	极限静态轴向载荷(磅)	动态摆动径向扭矩(磅)	估重(磅)
	球孔	外径	球头宽	衬套宽	"V" aperture diameter	Ball head end diameter	Ball diameter				
NSSB3V	0.19	0.5625	0.281	0.218	0.502	0.293	0.406	10	3,975	150	0.02
NSSB4V	0.25	0.6562	0.343	0.25	0.596	0.364	0.5	10	6.04	430	0.02
NSSB5V	0.3125	0.75	0.375	0.281	0.652	0.419	0.562	10	8,750	700	0.03
NSSB6V	0.375	0.8125	0.406	0.312	0.714	0.515	0.656	9	10,540	1,100	0.04
NSSB7V	0.4375	0.9062	0.437	0.343	0.808	0.57	0.718	8	13,200	1.4	0.05
NSSB8V	0.5	1	0.5	0.39	0.878	0.641	0.813	8	17,900	2,100	0.07
NSSB10V	0.625	1.1875	0.625	0.5	1.065	0.739	0.968	8	30,500	4,720	0.12
NSSB12V	0.75	1.4375	0.75	0.593	1.315	0.92	1.187	8	46,400	6,750	0.21
NSSB14V	0.875	1.5625	0.875	0.703	1.44	0.978	1.312	8	62,200	9,350	0.27
NSSB16V	1	1.75	1	0.797	1.628	1.118	1.5	9	82,200	12,160	0.39