

Bearing Designation	Dimensions(in)									Weight
轴承	尺寸 (英寸)									估重
steel to steel	D	T	W	O	M	Ball	Misalign.	Ult.Raidal	Approx.	(磅)
钢对钢	+0.000	±.005	±.005	Shoulder.	Chamfer	Dia.	Angle	Static	Brg.Wt.	
	-0.0007			Dia. Ref.	Ref	Ref.	a°	Load Lbs.	Lbs.	
SCOM2	0.165	0.4687	0.187	0.25	0.235	0.02	0.343	9	3,200	0.01
SCOM3	0.19	0.5625	0.218	0.281	0.293	0.02	0.406	11	4.4	0.01
SCOM4	0.25	0.6562	0.25	0.343	0.364	0.022	0.5	13.5	6,700	0.02
SCOM5	0.3125	0.75	0.281	0.375	0.419	0.032	0.562	12	9.2	0.03
SCOM6	0.375	0.8125	0.312	0.406	0.516	0.032	0.656	10	12,400	0.04
SCOM7	0.4375	0.9062	0.343	0.437	0.53	0.032	0.718	8	14,900	0.05
SCOM8	0.5	1	0.39	0.5	0.64	0.032	0.813	9.5	17,900	0.07
SCOM9	0.5625	1.0937	0.437	0.562	0.71	0.032	0.906	9.5	23,700	0.09
SCOM10	0.625	1.1875	0.5	0.625	0.78	0.032	1	8.5	32,000	0.11
SCOM12	0.75	1.4375	0.593	0.75	0.92	0.044	1.187	9	48,000	0.2
SCOM14	0.875	1.5625	0.703	0.875	0.98	0.044	1.312	9.5	69,000	0.26
SCOM16	1	1.75	0.797	1	1.118	0.044	1.5	10	83,000	0.39