

Bearing Designation	Dimensions(in)									Weight
轴承	尺寸(英寸)									估重
belt PTFE liner	D	T	W	O	M	Ball	Misaligh.	Ult.Raidal	Approx.	
带PTFE衬垫	+0.000	±0.005	±0.005	Shoulder.	Chamfer	Dia.	Angle	Static	Brg.Wt.	(磅)
	-0.0007			Dia. Ref.	Ref	Ref.	a°	Load Lbs.	Lbs.	
SCOM3T	0.19	0.5625	0.218	0.281	0.293	0.02	0.406	11	4,400	0.01
SCOM4T	0.25	0.6562	0.25	0.343	0.364	0.022	0.5	13.5	6,700	0.02
SCOM5T	0.3125	0.75	0.281	0.375	0.419	0.032	0.562	12	9,200	0.03
SCOM6T	0.375	0.8125	0.312	0.406	0.516	0.032	0.656	10	12.4	0.04
SCOM7T	0.4375	0.9062	0.343	0.437	0.53	0.032	0.718	8	14.9	0.05
SCOM8T	0.5	1	0.39	0.5	0.64	0.032	0.813	9.5	17,900	0.07
SCOM9T	0.5625	1.0937	0.437	0.562	0.71	0.032	0.906	9.5	23,700	0.09
SCOM10T	0.625	1.1875	0.5	0.625	0.78	0.032	1	8.5	32,000	0.11
SCOM12T	0.75	1.4375	0.593	0.75	0.92	0.044	1.187	9	48	0.2
SCOM14T	0.875	1.5625	0.703	0.875	0.98	0.044	1.312	9.5	69,000	0.26
SCOM16T	1	1.75	0.797	1	1.118	0.044	1.5	10	83,000	0.39