

Designation	Rated torque [N·m]	最大容许误差 Margin of error		Moment of inertia	The torque stiffness	The axial spring rigidity	Radial spring rigidity	Weight	A	B	C	D1/2	E(Locking torque)		F	G
		Eccentricity[mm]	Deflection										E (螺栓锁紧扭矩 N·m)			
型号	额定扭矩 [N·m]	偏心 [mm]	轴向位移 [m·m]	惯性力矩 [10·3N·m/rad]	扭矩刚性 [103N·m/rad]	轴向弹簧刚性 [N/mm]	径向弹簧刚性 [N/mm]	质量 [kg]					E (螺栓锁紧扭矩 N·m)			
LC-F3-15-48	15	0.15	1	0.12	20	25	475	0.25	48	49	19	10-22	M4	3	M4	49
LC-F3-15-55	15	0.2	2	0.59	15	15	137	0.25	55	49	19	10-22	M4	3	M4	49
LC-F3-30-57	30	0.2	1	0.3	39	50	900	0.4	57	55	22	12-23	M5	6	M4	55
LC-F3-30-65	30	0.25	2	0.34	28	30	270	0.4	65	55	22	12-23	M5	6	M4	55
LC-F3-60-66	60	0.2	1.5	0.54	76	72	1200	0.8	66	66	27	12-29	M5	8	M5	66
LC-F3-60-76	60	0.25	2	0.73	55	48	420	0.8	76	66	27	12-29	M5	8	M5	66
LC-F3-80-74	80	0.2	2	1.1	129	48	920	1.2	74	81	32	15-38	M6	10	M5	81
LC-F3-80-86	80	0.25	3	1.5	85	32	290	1.2	86	81	32	15-38	M6	10	M5	81
LC-F3-150-75	150	0.2	2	1.2	175	82	1550	1.2	75	81	32	15-38	M6	12	M5	81
LC-F3-150-87	150	0.25	3	1.6	110	52	435	1.2	87	81	32	15-38	M6	12	M5	81
LC-F3-200-78	200	0.25	2	1.7	191	90	2040	1.8	78	90	32	15-44	M6	14	M6	90
LC-F3-200-90	200	0.3	3	2.5	140	60	610	1.8	90	90	32	15-44	M6	14	M6	90
LC-F3-300-89	300	0.25	2.5	2.95	501	105	3750	3	89	110	41	24-56	M8	18	M6	110
LC-F3-300-103	300	0.3	3.5	5.8	350	71	1050	3	103	110	41	24-56	M8	18	M6	110
LC-F3-500-97	500	0.3	2.5	9.1	510	70	2500	4.2	97	123	41	24-60	M8	23	M6	122
LC-F3-500-110	500	0.35	3.5	9.9	500	48	840	4.2	110	123	41	24-60	M8	23	M6	122
LC-F3-800-114	800	0.35	3.5	13.2	780	100	2000	5.6	114	133	50	30-60	M10	40	M6	120
LC-F3-1500-141	1500	0.35	3.5	34.9	1304	195	3600	8.2	141	157	61	35-70	M12	70	M8	145
LC-F3-4000-195	4000	0.4	3.5	85.5	3400	565	6070	23	195	200	80	50-100	M16	120	M10	175
LC-F3-6000-210	6000	0.4	3	254	5700	1030	19200	32.6	210	253	85	60-140	M16	150	M10	246
LC-F3-10000-217	10000	0.4	3	629	10950	985	21800	45.5	217	303	92	70-180	8×M16	160	4×M10	295