

轴承代号	外形尺寸				基本额定载荷		重量	安装尺寸			极限转速	
Designation	Dimensions (mm)				Basic load rating (kN)		Weight(kg)	Mounting dimensions (mm)			Limiting Speed (r/min)	
	d	D	B	Tmin	Cr	Cor		damin	Dam ax	Tamax	脂	油
61820	100	125	13	1	19.6	21.2	0.31	105	120	1	4800	5700
61822	110	140	16	1	28.1	30.7	0.61	115	135	1	4300	5100
61824	120	150	16	1	29	33	0.66	125	145	1	4000	4700
61826	130	165	18	1.1	36.9	41.2	0.94	136.5	158.5	1	3600	4300
61828	140	175	18	1.1	38.2	44.4	1	146.5	168.5	1	3400	4000
61830	150	190	20	1.1	49.1	58.5	1.15	156.6	183.5	1	3000	3600
61832	160	200	20	1.1	48.5	61	1.23	166.5	193.5	1	2800	3400
61834	170	215	22	1.1	61.5	78	1.9	176.5	208.5	1	2600	3200
61836	180	225	22	1.1	62.3	78.5	1.72	186.5	218.5	1	2400	3000
61838	190	240	24	1.5	75.1	93.5	2.53	198	232	1.5	2200	2800
61840	200	250	24	1.5	74	98	2.67	208	242	1.5	2200	2800
61844	220	270	24	1.5	76.5	97.8	2.9	228	262	1.5	1900	2400
61848	240	300	28	2	83.5	108	4.48	249	291	2	1800	2200
61852	260	320	28	2	101	148	4.84	269	311	2	1700	2000
61856	280	350	33	2	133	191	7.2	289	341	2	1600	1900
61860	300	380	38	2.1	166	233	10.3	311	369	2	1400	1700
61864	320	400	38	2.1	168	244	10.8	331	389	2	1300	1600
61868	340	420	38	2.1	175	265	11.5	351	409	2	1200	1500
61872	360	440	38	2.1	192	290	11.8	371	429	2	1100	1400
61876	380	480	46	2.1	238	375	19.5	391	469	2	1000	1300
61880	400	500	46	2.1	241	390	20.5	411	489	2	1000	1300
61884	420	520	46	2.1	245	410	21.4	431	509	2	950	1200
61888	440	540	46	2.1	249	425	22.3	451	529	2	900	1100
61892	460	580	56	3	310	550	34.3	473	567	2.5	900	1100
61896	480	600	56	3	315	575	35.4	493	587	2.5	850	1000
618/500	500	620	56	3	320	600	37.2	513	607	2.5	800	950
618/530	530	650	56	3	325	625	39.8	543	637	2.5	750	900
618/560	560	680	56	3	330	650	41.5	573	667	2.5	700	850
618/600	600	730	60	3	355	735	50.9	613	717	2.5	670	800
618/710	710	870	74	4	480	1100	92.6	726	854	3	530	630
618/750	750	920	78	5	525	1260	110	770	900	4	500	600
618/800	800	980	82	5	530	1310	132	820	960	4	450	530
618/850	850	1030	82	5	559	1430	140	868	1012	4	410	470
618/900	900	1090	85	5	618	1532	160	920	1070	4	350	410
618/950	950	1150	90	5	637	1730	190	968	1132	4	290	350