

Bearing Designation	Dimensions						Limited static radial load (pounds)	Limited static axial load (pounds)	Dynamic swing radial torque (pounds)	Weight
	B	D	T	O	REF	a°				
型号	0	0	±.005	REF			极限静态径向载荷 (磅)	极限静态轴向载荷 (磅)	动态摆动径向扭矩 (磅)	估重 (磅)
	-0.0005	0.0005		"V"槽直径	球头端面直径	球径				
	球孔	外径	球头宽	"V" aperture diameter	Ball head end diameter	Ball diameter				
YSSB4	0.25	0.74	0.593	0.255	0.39	0.593	24	7,100	450	3,800
YSSB5	0.3125	0.6875	0.625	0.255	0.418	0.593	20	9,000	450	3,800
YSSB6	0.375	0.906	0.813	0.345	0.512	0.781	23	16,000	2	7,200
YSSB7	0.4375	1	0.875	0.345	0.618	0.875	22	19,300	2,000	8,100
YSSB8	0.5	1.125	0.937	0.401	0.73	1	20	26,100	3,200	10,900
YSSB10	0.625	1.375	1.2	0.567	0.856	1.25	20	44,500	7,000	20,000
YSSB12	0.75	1.5625	1.28	0.62	0.97	1.375	18	54.8	8,700	24,200