

Bearing Designation	Dimensions(mm/in)										Load rating(KN)	
	尺寸(mm/英寸)										载荷(KN)	
轴承型号	d	D	B	c	T	dk	s	A	rs r1s	α°	Dynamic Load	Static Load
									min	≈		
GACZ12S	12.7	22.225	6.86	4.83	7.62	18.26	1.3	2.39	0.51	7	18	0.013
GACZ12S	0.5	0.875	0.27	0.19	0.3	0.719	0.051	0.094	0.02	7	18	0.013
GACZ15S	15.875	26.988	8.64	6.35	9.4	22.83	1.48	2.77	0.76	6	31	0.025
GACZ15S	0.625	1.0625	0.34	0.25	0.37	0.899	0.058	0.109	0.03	6	31	0.025
GACZ19S	19.05	31.75	10.41	7.87	11.18	27.43	1.79	3.18	1	6	47	0.038
GACZ19S	0.75	1.25	0.41	0.31	0.44	1.08	0.07	0.125	0.04	6	47	0.038
GACZ22S	22.225	36.512	12.19	9.65	13.21	31.95	2.02	4.37	2	5.5	66	0.049
GACZ22S	0.875	1.4375	0.48	0.38	0.52	1.258	0.08	0.172	0.08	5.5	66	0.049
GACZ25S	25.4	41.275	13.97	11.18	15.24	36.5	2.54	5.16	2	6	87	0.085
GACZ25S	1	1.625	0.55	0.44	0.6	1.437	0.1	0.203	0.08	6	87	0.085
GACZ31S	31.75	50.8	17.78	13.97	18.8	45.59	3.36	5.94	2	6	142	0.159
GACZ31S	1.25	2	0.7	0.55	0.74	1.795	0.132	0.234	0.08	6	142	0.159
GACZ34S	34.925	55.562	19.56	15.24	21.34	49.2	3.69	7.14	2.54	4	159	0.213
GACZ34S	1.375	2.1875	0.77	0.6	0.84	1.937	0.145	0.281	0.1	4	159	0.213
GACZ38S	38.1	61.912	21.34	16.76	23.11	54.74	3.93	7.92	2.54	5.5	197	0.301
GACZ38S	1.5	2.4375	0.84	0.66	0.91	2.155	0.155	0.312	0.1	5.5	197	0.301
GACZ44S	44.45	71.438	24.89	20.07	27.18	63.88	4.72	8.33	2.54	6	273	0.458
GACZ44S	1.75	2.8125	0.98	0.79	1.07	2.515	0.186	0.328	0.1	6	273	0.458
GACZ50S	50.8	80.962	28.7	23.37	31.24	73.02	5.51	9.52	3.56	5.5	365	0.671
GACZ50S	2	3.1875	1.13	0.92	1.23	2.875	0.217	0.375	0.14	5.5	365	0.671
GACZ57S	57.15	90.488	32.26	26.67	35.31	82.17	6.18	11.51	3.56	5.5	466	0.948
GACZ57S	2.25	3.5625	1.27	1.05	1.39	3.235	0.243	0.453	0.14	5.5	466	0.948
GACZ63S	63.5	100.013	36.07	29.97	39.12	91.19	6.79	12.7	3.56	5	589	1.13
GACZ63S	2.5	3.9375	1.42	1.18	1.54	3.59	0.267	0.5	0.14	5	589	1.13
GACZ69S	69.85	111.125	39.62	32.38	43.18	100.33	7.46	13.08	4.6	5	694	1.75
GACZ69S	2.75	4.375	1.56	1.275	1.7	3.95	0.294	0.515	0.18	5	694	1.75
GACZ76S	76.2	120.65	43.43	35.69	47.24	109.52	8.17	14.68	4.6	5	838	2.28
GACZ76S	3	4.75	1.71	1.405	1.86	4.312	0.322	0.578	0.18	5	838	2.28
GACZ82S	82.55	130.175	47.24	39.24	51.56	118.74	9.04	16.66	4.6	5	995	2.89
GACZ82S	3.25	5.125	1.86	1.545	2.03	4.675	0.356	0.656	0.18	5	995	2.89
GACZ88S	88.9	139.7	50.8	42.54	55.37	128.02	9.51	17.86	4.6	5	1167	3.57
GACZ88S	3.5	5.5	2	1.675	2.18	5.04	0.374	0.703	0.18	5	1167	3.57
GACZ95S	95.25	149.225	54.61	45.85	59.44	136.91	10.1	19.43	4.6	4.5	1348	4.35
GACZ95S	3.75	5.875	2.15	1.805	2.34	5.39	0.398	0.765	0.18	4.5	1348	4.35
GACZ101S	101.6	158.75	58.42	49.15	63.5	146.05	10.4	19.84	4.6	4.5	1545	5.26
GACZ101S	4	6.25	2.3	1.935	2.5	5.75	0.409	0.781	0.18	4.5	1545	5.26
GACZ114S	114.3	177.8	65.79	55.75	71.12	164.46	12.4	22.22	4.6	4.5	1990	7.76
GACZ114S	4.5	7	2.59	2.195	2.8	6.475	0.488	0.875	0.18	4.5	1990	7.76
GACZ127S	127	196.85	73.15	62.36	79.5	182.63	13.9	25.4	4.6	4.5	2445	11.07
GACZ127S	5	7.75	2.88	2.455	3.13	7.19	0.547	1	0.18	4.5	2445	11.07
GACZ152S	152.4	222.25	78.74	66.42	85.72	207.16	16.1	34.8	4.6	4.5	2955	17.37
GACZ152S	6	8.75	3.1	2.615	3.375	8.156	0.634	1.37	0.18	4.5	2955	17.37