

Bearing Designation	Dimensions(mm)											Load rating(KN)		Weight	
	尺寸(mm)											载荷(KN)			重量
	d	D	H	B	c	dk	d2	D1	A	s	rs	Dynamic Load	Static Load		
min							max	动载				静载			
GX10S	10	30	9.5	7.5	7	32	15.5	27.5	3	7	27	136	9	0.036	
GX12S	12	35	13	9.5	9.3	38	18	32	4	8	37	188	8	0.072	
GX15S	15	42	15	11	10.8	46	22.5	39	5	10	53	267	8	0.108	
GX17S	17	47	16	11.8	11.2	52	27	43.5	5	11	61	311	10	0.137	
GX20S	20	55	20	14.5	13.8	60	31	50	6	12.5	84	425	9	0.246	
GX25S	25	62	22.5	16.5	16.7	68	34.5	58.5	6	14	134	672	7	0.415	
GX30S	30	75	26	19	19	82	42	70	8	17.5	182	909	7	0.614	
GX35S	35	90	28	22	20.7	98	50.5	84	8	22	266	1330	8	0.973	
GX40S	40	105	32	27	21.5	114	59	97	9	24.5	357	1810	9	1.59	
GX45S	45	120	36.5	31	25.5	128	67	110	11	27.5	486	2470	9	2.24	
GX50S	50	130	42.5	33	30.5	139	70	120	11	30	554	2810	7	3.14	
GX60S	60	150	45	37	34	160	84	140	12.5	35	748	3820	8	4.63	
GX70S	70	160	50	42	36.5	176	94.5	153	13.5	35	902	4610	8	5.37	
GX80S	80	180	50	43.5	38	197	107.5	172	14.5	42.5	1110	5700	8	6.91	
GX100S	100	210	59	51	46	222	127	198	15	45	1300	6470	8	10.9	
GX120S	120	230	64	53.5	50	250	145	220	16.5	52.5	1530	7580	6	13.9	
GX140S	140	260	72	61	54	274	177	243	23	52.5	1820	9040	6	18.1	
GX160S	160	290	77	66	58	313	200	271	23	65	2100	10440	7	23.2	
GX180S	180	320	86	74	62	340	225	299	26	67.5	2430	12070	8	30.9	
GX200S	200	340	87	80	66	365	247	320	27	70	3070	15280	8	34.2	