

Bearing Number	Size		Overrunning speeds		Dn6	D ₅	D ₆	L	t	b ^{H11}	r	r ₁	Weight
	尺寸		极限速度										重量
型号	d _{H7}	T _{KN}	n _{imax}	n _{amax}	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(Kg)
	(mm)	(Nm)	min ⁻¹	min ⁻¹									(Kg)
NF8	8	20	5000	6000	37	30	20	20	3	6	1,0	1,5	0,1
NF12	12	20	5000	6000	37	30	20	20	3	6	1,0	1,5	0,1
NF15	15	78	4500	5400	47	37	26	30	3,5	7	1,5	1,5	0,3
NF20	20	188	3000	3600	62	52	37	36	3,5	8	2,0	2,0	0,6
NF25	25	250	2200	2600	80	68	49	40	4	9	2,5	2,0	1,1
NF30	30	500	1800	2100	90	75	52,5	48	5	12	2,5	2,0	1,6
NF35	35	663	1600	1950	100	80	58	53	6	13	2,5	2,5	2,3
NF40	40	1100	1250	1700	110	90	62	63	7	15	3,0	2,5	3,1
NF45	45	1500	1100	1500	120	95	69	63	7	16	3,0	2,5	3,7
NF50	50	2375	850	1300	130	110	82	80	8,5	17	3,5	3,0	5,4
NF55	55	2500	800	1200	140	115	83	80	9	18	3,5	3,0	6,1
NF60	60	4250	700	1100	150	125	93,5	95	9	18	3,5	3,5	8,5
NF70	70	5875	620	900	170	140	106	110	9	20	3,5	3,5	13,0
NF80	80	10000	550	800	190	160	122	125	9	20	4,0	3,5	18,0
NF90	90	17250	480	700	215	180	133	140	11,5	24	4,0	4,0	25,3
NF100	100	19625	400	600	260	210	157	150	14,5	28	4,0	4,0	42,1
NF130	130	34750	300	480	300	240	188	180	17	32	5,0	5,0	65,0
NF150	150	44375	250	400	320	260	205	180	17	32	5,0	5,0	95,0